

NASA CR-170546

**DOCUMENT NO. 81SDS4226
AUGUST 1981**

"Made available under NASA sponsorship
in the interest of rapid and wide dis-
semination of Earth Resources Survey
Program information and without liability
for any use made thereof."

E83-10281


LANDSAT-D ORBITAL JITTER ANALYSIS

FINAL REPORT

(E83-10281) LANDSAT-D MSS/TH TUNED ORBITAL
JITTER ANALYSIS MODEL LDS900 Final Report
(General Electric Co.) 150 p HC A07/MF A01
CSCL 05B

N83-26148

**Unclas
G3/43 00281**



NAS-S-25300



GENERAL  ELECTRIC

BEST AVAILABLE COPY

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT-D FINAL MSS/TM TUNED
ORBITAL JITTER ANALYSIS
MODEL LSD900

PREPARED BY: T. E. Pollak
T. E. Pollak
Structural Dynamics

APPROVED BY: E. J. Kuhar
E. J. Kuhar, Lead Engineer
Structural Dynamics

APPROVED BY: J. R. Schumacher
J. R. Schumacher
Landsat-D Manager
Mechanical Systems

APPROVED BY: C. V. Stahle
C. V. Stahle, Manager
Structural Dynamics

TABLE OF CONTENTS

<u>SECTION</u>	<u>TITLE</u>	<u>PAGE</u>
1	SUMMARY.	1-1
2	CONCLUSIONS.	2-1
3	RECOMMENDATIONS.	3-1
4	DISCUSSION	4-1
	4.1 Model Description	4-1
	4.2 TDRSS Boom Re-Tuning.	4-31
	4.3 Response Data	4-35
5	ORBITAL ANALYSIS	5-1
	5.1 Orbital Analysis Approach	5-1
	5.2 Baseline Orbital Model - LSD900	5-3
	5.3 Worst Case Statistical Analysis	5-68
6	REFERENCES	6-1

ORIGINAL PAGE 13
OF POOR QUALITY

LIST OF FIGURES

<u>NUMBER</u>	<u>TITLE</u>	<u>PAGE</u>
4.1-1	Orbital Configuration.	4-3
4.1-2	Deployed Solar Array Representation.	4-11
4.1-3	Updated MMS Representation	4-15
4.1-4	Deployed TDRSS Boom Representation	4-18
4.1-5	Deployed RF Compartment Representation	4-20
4.1-6	Deployed TRW Supplied Ku/S-Band Antenna.	4-21
4.1-7	Updated Instrument Module Representation	4-27
4.2-1	Re-Tuned TDRSS Boom Analytical Mode No. 1.	4-38
4.2-2	Re-Tuned TDRSS Boom Analytical Mode No. 2.	4-39
4.2-3	Re-Tuned TDRSS Boom Analytical Mode No. 3.	4-40
4.2-4	Re-Tuned TDRSS Boom Analytical Mode No. 4.	4-41
4.2-5	Re-Tuned TDRSS Boom Analytical Mode No. 5.	4-42
4.2-6	Re-Tuned TDRSS Boom Analytical Mode No. 6.	4-43
4.2-7	Re-Tuned TDRSS Boom Analytical Mode No. 7.	4-44
5.1-1	MSS/TM Bandwidth Considerations.	5-2
5.2-1	Orbital Model LSD900 Analytical Mode No. 7	5-5
5.2-2	Orbital Model LSD900 Analytical Mode No. 8	5-6
5.2-3	Orbital Model LSD900 Analytical Mode No. 9	5-7
5.2-4	Orbital Model LSD900 Analytical Mode No. 10.	5-8
5.2-5	Orbital Model LSD900 Analytical Mode No. 11.	5-9
5.2-6	Orbital Model LSD900 Analytical Mode No. 12.	5-10
5.2-7	Orbital Model LSD900 Analytical Mode No. 13.	5-11
5.2-8	Orbital Model LSD900 Analytical Mode No. 14.	5-12
5.2-9	Orbital Model LSD900 Analytical Mode No. 15.	5-13
5.2-10	Orbital Model LSD900 Analytical Mode No. 16.	5-14
5.2-11	Orbital Model LSD900 Analytical Mode No. 17.	5-15
5.2-12	Orbital Model LSD900 Analytical Mode No. 18.	5-16
5.2-13	Orbital Model LSD900 Analytical Mode No. 19.	5-17
5.2-14	Orbital Model LSD900 Analytical Mode No. 20.	5-18
5.2-15	Orbital Model LSD900 Analytical Mode No. 21.	5-19
5.2-16	Orbital Model LSD900 Analytical Mode No. 22.	5-20
5.2-17	Orbital Model LSD900 Analytical Mode No. 23.	5-21
5.2-18	Orbital Model LSD900 Analytical Mode No. 24.	5-22
5.2-19	Orbital Model LSD900 Analytical Mode No. 25.	5-23
5.2-20	Orbital Model LSD900 Analytical Mode No. 26.	5-24
5.2-21	Force At TM Theta X - Response At MSS Theta X (0-100 Hz) Damping = 0.001	5-26
5.2-22	Force At TM Theta X - Response At MSS Theta X (100-200 Hz) Damping = 0.001	5-27
5.2-23	Force At TM Theta X - Response At MSS Theta Y (0-100 Hz) Damping = 0.001	5-28
5.2-24	Force At TM Theta X - Response At MSS Theta Y (100-200 Hz) Damping = 0.001	5-29
5.2-25	Force At TM Theta X - Response At MSS Theta Z (0-100 Hz) Damping = 0.001	5-30

LIST OF FIGURES (CONTINUED)

<u>NUMBER</u>	<u>TITLE</u>	<u>PAGE</u>
5.2-26	Force At TM Theta X - Response At MSS Theta Z (100-200 Hz)	5-31
5.2-27	Force And Response At MSS Theta X (0-100 Hz) Damping = 0.001	5-32
5.2-28	Force And Response At MSS Theta X (100-200 Hz) Damping = 0.001	5-33
5.2-29	Force At MSS Theta X - Response At MSS Theta Y (0-100 Hz) Damping = 0.001.	5-34
5.2-30	Force At MSS Theta X - Response At MSS Theta Y (100-200 Hz) Damping = 0.001.	5-35
5.2-31	Force At MSS Theta X - Response At MSS Theta Z (0-100 Hz) Damping = 0.001.	5-36
5.2-32	Force At MSS Theta X - Response At MSS Theta Z (100-200 Hz) Damping = 0.001.	5-37
5.2-33	Force At TM Theta X - Response At MSS Theta X (0-100 Hz) Damping = 0.01	5-39
5.2-34	Force At TM Theta X - Response At MSS Theta X (100-200 Hz) Damping = 0.01	5-40
5.2-35	Force At TM Theta X - Response At MSS Theta Y (0-100 Hz) Damping = 0.01	5-41
5.2-36	Force At TM Theta X - Response At MSS Theta Y (100-200 Hz) Damping = 0.01	5-42
5.2-37	Force At TM Theta X - Response At MSS Theta Z (0-100 Hz) Damping = 0.01	5-43
5.2-38	Force At TM Theta X - Response At MSS Theta Z (100-200 Hz) Damping = 0.01	5-44
5.2-39	Force and Response At MSS Theta X (0-100 Hz) Damping = 0.01.	5-45
5.2-40	Force and Response At MSS Theta X (100-200 Hz) Damping = 0.01.	5-46
5.2-41	Force At MSS Theta X - Response At MSS Theta Y (0- 100 Hz) Damping = 0.01.	5-47
5.2-42	Force At MSS Theta X - Response At MSS Theta Y (100- 200 Hz) Damping = 0.01.	5-48
5.2-43	Force At MSS Theta X - Response At MSS Theta Z (0- 100 Hz) Damping = 0.01.	5-49
5.2-44	Force At MSS Theta X - Response At MSS Theta Z (100- 200 Hz) Damping = 0.01.	5-50
5.2-45a-b	Typical Response Showing 5% Bandwidth For MSS (0-200 Hz).	5-62-5-63
5.2-46a-b	Typical Response Showing 10% Bandwidth For MSS (0-200 Hz).	5-64-5-65
5.2-47a-b	Typical Response Showing 15% Bandwidth For MSS (0-200 Hz).	5-66-5-67

ORIGINAL PAGE IS
OF POOR QUALITY

LIST OF FIGURES (CONTINUED)

<u>NUMBER</u>	<u>TITLE</u>	<u>PAGE</u>
5.3-1	Gaussian Probability Density Function.	5-71
5.3-2	Probability of Exceeding X Arc-Sec of Jitter	5-72
5.3-3	Theta X Probability of Exceeding Jitter Response - MSS Force - Damping = 0.001	5-75
5.3-4	Theta Y Probability of Exceeding Jitter Response - MSS Force - Damping = 0.001	5-76
5.3-5	Theta Z Probability of Exceeding Jitter Response - MSS Force - Damping = 0.001	5-77
5.3-6	Theta X Probability of Exceeding Jitter Response - TM Force - Damping = 0.001.	5-78
5.3-7	Theta Y Probability of Exceeding Jitter Response - TM Force - Damping = 0.001.	5-79
5.3-8	Theta Z Probability of Exceeding Jitter Response - TM Force - Damping = 0.001.	5-80
5.3-9	Theta X Probability of Exceeding Jitter Response - MSS Force - Damping = 0.01.	5-81
5.3-10	Theta Y Probability of Exceeding Jitter Response - MSS Force - Damping = 0.01.	5-82
5.3-11	Theta Z Probability of Exceeding Jitter Response - MSS Force - Damping = 0.01.	5-83

LIST OF TABLES

<u>NUMBER</u>	<u>TITLE</u>	<u>PAGE</u>
4.1-1	Substructure Representation.	4-2
4.1-2	Dynamic Model Summary Table.	4-5
4.1-3	DS/A Free-Free Dynamic Model Summary Table	4-12
4.1-4	Weight Breakdown For Updated MMS (Tuned)	4-16
4.1-5	MMS Free-Free Dynamic Model Summary Table.	4-17
4.1-6	GDA Stiffness Properties For Orbital Model LSD900.	4-19
4.1-7	Boom/RFC Free-Free Dynamic Model Summary Table	4-22
4.1-8	Ku/S-Band Free-Free Dynamic Model Summary Table.	4-23
4.1-9	TM and TM Foot Simulation.	4-25
4.1-10	IM Free-Free Dynamic Model Summary Table	4-28
4.1-11	Orbital Jitter Models Comparative Summary.	4-30
4.1-12	Appendage Coupling Stiffnesses	4-32
4.2-1	Changes For Re-Tuning 2nd Y-Bending Mode of Boom/ RFC NASTRAN Model.	4-33
4.2-2	Comparison of Measured To Tuned NASTRAN Modal Frequency Values	4-34
4.2-3	Self-Ortho Check Of Tuned Analytical Model (306 DOF) Truncated To 42 DOF Test Set	4-36
4.2-4	Re-Tuned TDRSS Boom Mode Identification.	4-37
4.2-5	Landsat-D Deployed TDRSS Boom Cross Orthogonality Between Measured Modes and Tuned Analytical Model.	4-45
4.3-1	Representative Nodes In Data Transmittal to ACS.	4-46
4.3-2	Structural Transfer Function Coefficient Values For Orbital Model LSD900 - Damping = 0.001	4-47
4.3-3	Structural Transfer Function Coefficient Values For Orbital Model LSD900 - Damping = 0.01.	5-41
5.2-1	LS/D Final Tuned Orbital Model For Jitter - LSD900	5-4
5.2-2	LSD900 Transfer Function Data Presentation - Damping = 0.001.	5-25
5.2-3	LSD900 Transfer Function Data Presentation - Damping = 0.01	5-38
5.2-4	Jitter Allowables.	5-51
5.2-5	TM Forces - MSS/RMS Allowables - Damping = 0.001 - 15% BW	5-52
5.2-6	TM Forces - MSS/RMS Allowables - Damping = 0.001 - 10% BW	5-53
5.2-7	TM Forces - MSS/RMS Allowables - Damping = 0.001 - 5% BW.	5-54
5.2-8	MSS Forces - MSS/RMS Allowables - Damping = 0.001 - 15% BW	5-55
5.2-9	MSS Forces - MSS/RMS Allowables - Damping = 0.001 - 10% BW	5-56

LIST OF TABLES (CONTINUED)

<u>NUMBER</u>	<u>TITLE</u>	<u>PAGE</u>
5.2-10	MSS Forces - MSS/RMS Allowables - Damping = 0.001 - 5% BW.	5-57
5.2-11	MSS Forces - MSS/RMS Allowables - Damping = 0.01 - 15% BW.	5-58
5.2-12	TM Forces - TM/Peak Allowables - Damping = 0.001 - 15% BW	5-60
5.2-13	MSS Forces- TM/Peak Allowables - Damping = 0.001 - 15% BW	5-61
5.2-14	LSD900 Baseline Jitter Predictions - Damping = 0.001.	5-69
5.2-15	LSD900 Baseline Jitter Predictions - Damping = 0.01	5-70

1.0 SUMMARY

The final Landsat-D orbital dynamic math model (LSD900), comprised of all test validated substructures, has been used to evaluate the jitter response of the MSS/TM experiments. The revisions to the previous analytical model, LSD801, include: (1) updated tuned MMS dynamic model to include dynamic test results from propulsion system testing; (2) test verified TDRSS boom/RF Compartment substructure with the boom 2nd Y-bending mode re-tuned to better match test data increasing the on-orbit frequency separation from the fundamental MSS forcing harmonic at 13.62 Hz; (3) updated coupling simulation between the MMS and Instrument Module substructures; and (4) updated IM dynamic model representing the design as shown on the released prints as of January 1981 and including the structural updates to the 36 and 55 bulkheads. No simulation updates were included in the TRW supplied RF Compartment and Ku/S-Band Antenna models over those of model LSD801. The appendage orientation used for this final analysis positions the Ku/S-Band antenna line-of-sight and deployed solar array solar cells along the Landsat-D -Z axis.

A dynamic forced response analysis was performed at both the MSS and TM locations on all structural modes considered (thru 200 Hz). The analysis determined the roll angular response of the MSS/TM experiments to impulsive excitation generated by component operation. Cross axis and cross experiment responses were also calculated. The excitations were analytically represented by seven and nine term Fourier series approximations, for the MSS and TM experiment respectively, which enabled linear harmonic solution techniques to be applied to response calculations.

For consistency in data presentation between previous and current orbital models, a damping value of 0.001 was assumed. However, recent spacecraft data acquisitions suggest larger damping values. Therefore, data is also presented herein for an assumed damping value of 0.01. The baseline orbital model has self-induced peak roll angular responses (damping = 0.001) of 2.0945 arc-seconds (MSS due to MSS) and 1.3725 arc-seconds (TM due to TM). These values translate, respectively, to rms values of 1.1673 and 0.8445 respectively.

Single mode worst case jitter was estimated by variations of the eigenvalue spectrum of model LSD900. These variations show the effect of possible structural frequency deviations from the best estimate of model LSD900 by modifying the modal spectrum so that the maximum resonant response of any one mode would be excited. Modes near each forcing harmonic which differed in frequency by more than 15% were not included in the analysis. Maximum worst case peak roll response for .001 damping was 94.55 arc-seconds which translates into a 65.54 arc-second rms response for the MSS. Third harmonic mode 105 exhibited this large response. Maximum worst case peak roll angular response for the TM experiment for all models considered and 0.001 damping was 6.63 arc-seconds or 3.99 arc-seconds rms. Since the peak response is within the capability of the adjustable gain ADS (angular displacement sensor), emphasis was shifted to MSS jitter amplitudes always noting, however, TM peak responses.

Since an analytical model cannot be tuned to exactly match all measured test modes and frequencies and the Landsat-D's structure may not exactly match the tested hardware, there is an uncertainty associated

with the analytical predicted frequencies. A statistical analysis approach was implemented to examine the probability of any worst case mode occurrence. The probability of exceeding the 1.5 arc-sec (.3 pixel error) in the θ_x direction is reduced from .34 to .093 if the allowable MSS RMS jitter is raised to 3.14 arc-sec (.4 pixel error), see Figure 5.3-3.

ORIGINAL PAGE IS
OF POOR QUALITY

2.0 CONCLUSIONS

- 1) All worst case TM jitter peak response amplitudes are within the capability of the ADS.
- 2) There is no requirement to modify the primary structure to de-tune structural resonances.
- 3) The Baseline MSS jitter meets the .3 pixel requirements.
- 4) Statistical analysis of MSS worst case jitter, using all test verified analytical substructure models shows a low probability of exceeding .3 pixel error $\approx 34\%$ and an even lower probability of exceeding .4 pixel error $\approx 9\%$ which meets the jitter criteria defined in SVS-9934 LSD Flight Segment Specification. The "probability" numbers noted indicate the probability that the given pixel error will be exceeded for any given flight when the TDRSS antenna and solar array are in their worst case orientation.
- 5) Simultaneous TM & MSS operation is feasible within the recommended jitter criteria.
- 6) Baseline jitter results are relatively insensitive to damping value changes between .001 and .01.
- 7) Statistical analysis results are highly sensitive to damping value changes between .001 and .01 for all pixel allowables.

3.0 RECOMMENDATIONS

1. The previously recommended all axis gain setting of 50 arc-seconds for the ADS should provide an ample error margin when using expected TM peak responses.
2. Should any major structural changes occur on the Landsat-D spacecraft, it is recommended that another orbital model be assembled to establish adherence to MSS jitter criterion values.

ORIGINAL PAGE IS
OF POOR QUALITY

4.0 DISCUSSION

4.1 MODEL DESCRIPTION

The latest Landsat-D orbital model used for evaluation of MSS/TM jitter has been LSD801 (Reference 1). To better assess MSS/TM orbital jitter predictions, an updated orbital model, LSD900, has been developed. This updated model differs from the previous model in that all test validated substructure models have been used. Also, the TDRSS boom modal test model was effectively retuned to match more closely the boom modal test. This increases the separation of the boom 2nd Y-bending mode from the first MSS forcing harmonic at 13.62 Hz. The test verified substructure models incorporated into model LSD900 include the IM centerbody, deployed solar array, deployed TDRSS boom/RF Compartment-Ku/S-Band Antenna, and NASA furnished MMS.

The Landsat-D Orbital Dynamic Math Model, LSD900, consists of six (6) primary substructures: Multi-Mission Modular Spacecraft (MMS); Instrument Module (IM) which includes Thematic Mapper (TM), Wideband Module (WB), and Multi-Spectral Scanner (MSS) components; deployed Solar Array (DS/A); and TDRSS boom which includes the RF Compartment (RFC) and Ku/S-Band Antenna. The dynamic math model consisting of 819 dynamic degrees of-freedom (DOF) and 257 nodes was obtained from a complex static model represented by 2700 nodes and 15187 static DOF. A node and DOF summary for each substructure is presented in Table 4.1-1. Figure 4.1-1 shows the orbital configuration (exploded at 3 structural interfaces, IM/MMS, RFC-Ku/S-Band Antenna, and TDRSS boom/RFC) for plotting clarity.

Table 4.1-1 Substructure Representation

Substructure	Before Reduction		After Reduction	
	Nodes	DOF's	Nodes	DOF's
MMS	659	3954	50	159
IM	957	5082	70	234
Deployed Solar Array	333	1951	60	150
Deployed TDRSS Boom With Detailed Outer Hinge	102	464	15	60
RF Compartment	323	1780	27	99
Ku/S-Band Antenna	326	1956	35	117
	Total Nodes:	2700	Total DOF:	15187
	Reduced Nodes:	2443	Reduced DOF:	14368
	Model Nodes:	257	Model DOF:	819

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE 18
OF POOR QUALITY




Figure 4.1-1 Orbital Configuration

ORIGINAL PAGE IS
OF POOR QUALITY

Stiffness coupling was used to assemble the 6 substructures. Table 4.1-2 summarizes nodes, node coordinates, DOF schedule, and nodal weights defined in the orbital model.

Substructure modeling changes reflect documented recommendations, released drawings and modal test results. Reference 2 documents the modal test results for the deployed solar array substructure. A representation of the deployed solar array structure is presented in Figure 4.1-2. Substructure DOF summary is shown in Table 4.1-3.

The original MMS substructure NASTRAN model as incorporated in model LSD801 was updated by NASA-Goddard for inclusion in the current configuration. The MMS substructure is described as three (3) primary modules, Power Module, Attitude Control Systems Module, and Command and Data Handling Module. The modules are connected to a triangular module support structure (MSS). The triangular transition adapter (TTA) located atop the MSS provides the interface attachment points for the Instrument Module structure. The Payload Attachment Fitting (PAF) is located beneath the MSS and provides the attachment to the launch vehicle. For the free-free orbital configuration, the PAF structure was deleted from the NASTRAN bulk data deck. Located within the MSS are the two primary propulsion tanks, PM1 and PM1A, and their associated attachment structures. The major improvement was the incorporation of dynamic test results to better represent the modeling simulation of the propulsion tanks and associated support structure. Also included is the earth sensor and the signal control and conditioning

DATE 070181
RUN BY T.E.POLLAK

RUN NO. LSD900

PHASE 3 JITTER ORBITAL MODEL
DYNAMIC MODEL SUMMARY TABLE
COORDINATES

DESC.	Syst. Node No.	COORDINATES			DOF TABLE			WEIGHT DATA									
		X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	1XX	1YY	1ZZ	
PELLA TANK	3000	-46.100	0.	0.	1	2	3	0	0	0	0	400.200	400.200	400.200	0.	0.	0.
	2 4600	-8.800	-25.981	-15.000	4	5	6	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
	3 4650	-61.000	-25.981	-15.000	7	8	9	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
	4 4682	-8.800	-21.075	-14.723	10	11	12	0	0	0	0	40.710	40.710	40.710	0.	0.	0.
	5 4692	-8.800	-14.723	-14.723	13	14	15	0	0	0	0	40.710	40.710	40.710	0.	0.	0.
	6 4700	-8.800	25.981	-15.000	16	17	18	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
	7 4750	-61.000	25.981	-15.000	19	20	21	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
	8 4782	-8.800	23.288	-10.890	22	23	24	0	0	0	0	43.447	43.447	43.447	0.	0.	0.
	9 4792	-8.800	2.213	25.613	25	26	27	0	0	0	0	43.447	43.447	43.447	0.	0.	0.
	10 4800	-8.800	0.	30.000	28	29	30	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
EARTH SHAKER	11 4850	-61.000	0.	30.000	31	32	33	0	0	0	0	41.630	41.630	41.630	0.	0.	0.
	12 4875	-24.900	0.	37.050	34	35	36	37	38	39	0	56.380	56.380	56.380	3600.00	2000.00	2500.00
	13 4878	-43.810	0.	37.800	40	41	42	43	44	45	0	26.000	26.000	26.000	500.00	400.00	400.00
	14 4882	-8.800	-2.213	25.613	46	47	48	0	0	0	0	24.665	24.665	24.665	0.	0.	0.
	15 4892	-8.800	-23.288	-10.890	49	50	51	0	0	0	0	24.665	24.665	24.665	0.	0.	0.
	16 5709	-3.200	0.	30.000	52	53	54	0	0	0	0	12.333	12.333	12.333	0.	0.	0.
	17 5737	-3.200	-25.981	-15.000	55	56	57	0	0	0	0	12.333	12.333	12.333	0.	0.	0.
	18 5765	-3.200	25.981	-15.000	58	59	60	0	0	0	0	12.333	12.333	12.333	0.	0.	0.
	19 6200	-56.800	-23.000	-14.723	61	62	63	0	0	0	0	31.300	31.300	31.300	0.	0.	0.
	20 6208	-56.800	-23.000	-31.723	64	65	66	0	0	0	0	23.760	23.760	23.760	0.	0.	0.
ACS	21 6228	-10.800	-23.000	-31.723	67	68	69	0	0	0	0	23.760	23.760	23.760	0.	0.	0.
	22 6316	-38.400	-13.800	-31.723	70	71	72	0	0	0	0	34.435	34.435	34.435	0.	0.	0.
	23 6320	-29.200	-13.800	-31.723	73	74	75	0	0	0	0	34.435	34.435	34.435	0.	0.	0.
	24 6616	-38.400	13.800	-31.723	76	77	78	0	0	0	0	34.435	34.435	34.435	0.	0.	0.
	25 6620	-29.200	13.800	-31.723	79	80	81	0	0	0	0	34.435	34.435	34.435	0.	0.	0.
	26 6700	-56.800	23.000	-14.723	82	83	84	0	0	0	0	31.300	31.300	31.300	0.	0.	0.
	27 6708	-56.800	23.000	-31.723	85	86	87	0	0	0	0	23.760	23.760	23.760	0.	0.	0.
	28 6728	-10.800	23.000	-31.723	88	89	90	0	0	0	0	23.760	23.760	23.760	0.	0.	0.
	29 6993	-33.800	3.000	-20.723	91	92	93	0	0	0	0	50.000	50.000	50.000	0.	0.	0.
	30 7200	-56.800	24.250	-12.557	94	95	96	0	0	0	0	34.547	34.547	34.547	0.	0.	0.
TOWER	31 7208	-56.800	38.972	-4.057	97	98	99	0	0	0	0	49.949	49.949	49.949	0.	0.	0.
	32 7228	-10.800	38.972	-4.057	100	101	102	0	0	0	0	6.591	6.591	6.591	0.	0.	0.
	33 7316	-38.400	34.372	3.910	103	104	105	0	0	0	0	128.046	128.046	128.046	0.	0.	0.
	34 7320	-29.200	34.372	3.910	106	107	108	0	0	0	0	27.663	27.663	27.663	0.	0.	0.
	35 7616	-38.400	20.572	27.812	109	110	111	0	0	0	0	146.583	146.583	146.583	0.	0.	0.
	36 7620	-29.200	20.572	27.812	112	113	114	0	0	0	0	19.772	19.772	19.772	0.	0.	0.
	37 7700	-56.800	1.250	27.280	115	116	117	0	0	0	0	34.547	34.547	34.547	0.	0.	0.
	38 7708	-56.800	15.972	35.780	118	119	120	0	0	0	0	46.682	46.682	46.682	0.	0.	0.
	39 7728	-10.800	15.972	35.780	121	122	123	0	0	0	0	9.220	9.220	9.220	0.	0.	0.
	40 8200	-56.800	-1.250	27.280	124	125	126	0	0	0	0	15.885	15.885	15.885	0.	0.	0.
CANTILEVER	41 8208	-56.800	-15.972	35.780	127	128	129	0	0	0	0	13.681	13.681	13.681	0.	0.	0.
	42 8228	-10.800	-15.972	35.780	130	131	132	0	0	0	0	13.681	13.681	13.681	0.	0.	0.
	43 8316	-38.400	-20.572	27.813	133	134	135	0	0	0	0	41.044	41.044	41.044	0.	0.	0.
	44 8320	-29.200	-20.572	27.813	136	137	138	0	0	0	0	41.044	41.044	41.044	0.	0.	0.
	45 8616	-38.400	-34.372	3.910	139	140	141	0	0	0	0	41.044	41.044	41.044	0.	0.	0.
	46 8620	-29.200	-34.372	3.910	142	143	144	0	0	0	0	41.044	41.044	41.044	0.	0.	0.
	47 8700	-56.800	-24.250	-12.557	145	146	147	0	0	0	0	15.885	15.885	15.885	0.	0.	0.
	48 8708	-56.800	-38.972	-4.057	148	149	150	0	0	0	0	13.681	13.681	13.681	0.	0.	0.
	49 8728	-10.800	-38.972	-4.057	151	152	153	0	0	0	0	13.681	13.681	13.681	0.	0.	0.
	50 9000	-71.700	0.	0.	154	155	156	157	158	159	0	337.000	337.000	337.000	71170.00	45240.00	35290.00

Table 4.1-2

RUN NO. LSD900

DATE 070181
RUN BY T.E.POLLAK

PHASE 3 JITTER ORBITAL MODEL
DYNAMIC MODEL SUMMARY TABLE

DESC.	Sat No.	Sat Name	X COORDINATES	X	Y	Z	RZ	WK	WY	WZ	WEIGHT DATA IXX IYY IZZ
Top	51	320	3.821	29.304	160	161	162	0	0	0	25.313 25.313 25.313
Or	52	328	8.000	26.540	163	164	165	0	0	0	17.125 17.125 17.125
Mission	53	338	8.000	-26.540	166	167	168	0	0	0	8.008 8.008 8.008
Abstar	54	346	8.000	-3.821	29.304	169	170	171	0	0	9.177 9.177 9.177
Th/ma	55	347	8.000	7.024	20.380	172	173	174	0	0	1.650 1.650 1.650
Atch	56	348	8.000	16.180	-3.550	175	176	177	0	0	1.680 1.680 1.680
Atch	57	349	8.000	-4.820	-11.580	178	179	180	0	0	3.200 3.200 3.200
Atch	58	350	8.000	-13.973	12.350	181	182	183	0	0	1.690 1.690 1.690
Bottom	59	420	0	3.821	29.023	184	185	186	0	0	23.123 23.123 23.123
Or	60	446	0	-3.821	29.023	187	188	189	0	0	7.785 7.785 7.785
Mission	61	460	0	23.224	-17.820	190	191	192	0	0	10.886 10.886 10.886
Abstar	62	461	0	27.045	-11.202	193	194	195	0	0	13.653 13.653 13.653
Atch	63	470	0	-23.224	-17.820	196	197	198	0	0	8.048 8.048 8.048
Atch	64	471	0	-27.045	-11.202	199	200	201	0	0	7.053 7.053 7.053
Top	65	1011	8.000	-21.000	-20.000	202	203	204	0	0	14.048 14.048 14.048
MA	66	1020	8.000	21.000	-20.000	205	206	207	0	0	12.593 12.593 12.593
MA	67	1034	19.250	-21.000	-20.000	208	209	210	0	0	11.426 11.426 11.426
MA	68	1043	19.250	21.000	-20.000	211	212	213	0	0	10.330 10.330 10.330
MA	69	1075	36.500	-21.000	-20.000	214	215	216	0	0	19.521 19.521 19.521
MA	70	1079	36.500	-5.500	-20.000	217	218	219	0	0	8.167 8.167 8.167
MA	71	1081	36.500	5.500	-20.000	220	221	222	0	0	7.194 7.194 7.194
MA	72	1085	36.500	21.000	-20.000	223	224	225	0	0	18.670 18.670 18.670
MA	73	1127	55.000	-21.000	-20.000	226	227	228	0	0	26.723 26.723 26.723
MA	74	1132	55.000	-5.500	-20.000	229	230	231	0	0	15.602 15.602 15.602
MA	75	1133	55.000	5.500	-20.000	232	233	234	0	0	19.651 19.651 19.651
MA	76	1136	55.000	21.000	-20.000	235	236	237	0	0	25.888 25.888 25.888
MA	77	1155	74.000	-21.000	-20.000	238	239	240	0	0	10.401 10.401 10.401
MA	78	1159	74.000	-5.500	-20.000	241	242	243	0	0	5.498 5.498 5.498
MA	79	1160	74.000	5.500	-20.000	244	245	246	0	0	13.359 13.359 13.359
MA	80	1163	74.000	21.000	-20.000	247	248	249	0	0	17.135 17.135 17.135
MA	81	1200	36.500	-21.000	-9.000	250	251	252	0	0	8.581 8.581 8.581
MA	82	1209	36.500	21.000	-9.000	253	254	255	0	0	10.535 10.535 10.535
MA	83	1269	55.000	-21.000	-9.000	256	257	258	0	0	17.738 17.738 17.738
MA	84	1279	55.000	21.000	-9.000	259	260	261	0	0	14.309 14.309 14.309
MA	85	1298	74.000	-21.000	-9.000	262	263	264	0	0	4.405 4.405 4.405
MA	86	1302	74.000	-5.500	-9.000	265	266	267	0	0	12.322 12.322 12.322
MA	87	1303	74.000	5.500	-9.000	268	269	270	0	0	12.322 12.322 12.322
MA	88	1306	74.000	21.000	-9.000	271	272	273	0	0	4.482 4.482 4.482
MA	89	1468	25.250	-18.000	-24.000	274	275	276	277	278	279
MA	90	1469	25.250	18.000	-24.000	280	281	282	283	284	285
MA	91	1482	76.250	-18.000	-21.000	286	287	288	289	290	291
MA	92	1495	76.250	18.000	-24.000	292	293	294	295	296	297
MA	93	1526	75.375	-11.215	-10.485	298	299	300	0	0	0
MA	94	1528	75.375	7.215	-10.485	301	302	303	0	0	0
MA	95	1529	75.375	-4.960	-21.250	304	305	306	0	0	0
MA	96	1530	75.375	4.960	-21.250	307	308	309	0	0	0
MA	97	1554	71.000	7.750	-5.000	310	311	312	0	0	0
MA	98	1555	60.500	7.750	-5.000	313	314	315	0	0	0
MA	99	1560	71.000	-6.250	-5.000	316	317	318	0	0	0
MA	100	1561	60.500	-6.250	-5.000	319	320	321	0	0	0

Table 4. (Continued)

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. LSD900

DATE 070181
RUN BY T.E.POLLAK

PHASE 3 JITTER ORBITAL MODEL DYNAMIC MODEL SUMMARY TABLE COORDINATES										DOF TABLE				WEIGHT DATA			
DESC	Stat. No.	X	Y	Z	X	Y	Z	RZ	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
ATTACH 101	1572	50.750	-21.000	-14.500	322.323	324.325	326.327	0	0	0	0	2.000	2.000	2.000	1.000	1.000	1.000
ATTACH 102	1621	53.920	-21.000	19.249	328.329	330.332	333.336	0	0	0	0	5.262	5.262	5.262	0.000	0.000	0.000
ATTACH 103	1633	53.920	21.000	19.249	331.332	333.336	336.339	0	0	0	0	6.415	6.415	6.415	0.000	0.000	0.000
ATTACH 104	1649	42.300	0.000	-16.500	334.335	336.339	339.342	0	0	0	0	22.629	22.629	22.629	44.000	44.000	44.000
ATTACH 105	1664	67.250	0.000	1.660	340.341	342.343	344.345	0	0	0	0	130.000	130.000	130.000	16181.000	7780.000	12724.000
ATTACH 106	1669	21.100	6.380	0.820	346.347	348.349	350.351	0	0	0	0	549.700	549.700	549.700	271300.000	95472.000	226617.000
ATTACH 107	1679	75.375	0.000	-16.250	352.353	354.357	357.360	0	0	0	0	2.971	2.971	2.971	0.000	0.000	0.000
ATTACH 108	30012	53.750	11.078	12.045	355.356	357.360	360.363	0	0	0	0	19.700	19.700	19.700	0.000	0.000	0.000
ATTACH 109	30014	53.750	-10.579	-12.045	358.359	361.364	364.367	0	0	0	0	3.935	3.935	3.935	0.000	0.000	0.000
ATTACH 110	30019	53.750	11.078	25.465	361.362	363.366	366.369	0	0	0	0	3.300	3.300	3.300	0.000	0.000	0.000
ATTACH 111	30021	53.750	-10.579	25.465	364.365	366.369	369.372	0	0	0	0	32.300	32.300	32.300	0.000	0.000	0.000
ATTACH 112	30060	37.750	11.078	12.045	367.368	369.372	372.375	0	0	0	0	35.600	35.600	35.600	0.000	0.000	0.000
ATTACH 113	30064	37.750	-10.579	12.045	370.371	372.375	375.378	0	0	0	0	3.635	3.635	3.635	0.000	0.000	0.000
ATTACH 114	30077	37.750	11.078	25.465	373.374	375.378	378.381	0	0	0	0	3.000	3.000	3.000	0.000	0.000	0.000
ATTACH 115	30081	37.750	-10.579	25.465	376.377	378.381	381.384	0	0	0	0	5.000	5.000	5.000	0.000	0.000	0.000
ATTACH 116	30152	46.250	0.250	28.986	379.380	381.384	384.387	0	0	0	0	7.200	7.200	7.200	0.000	0.000	0.000
ATTACH 117	30166	53.750	17.062	-9.500	382.383	384.387	387.390	0	0	0	0	10.400	10.400	10.400	0.000	0.000	0.000
ATTACH 118	30167	53.750	-16.563	-9.500	385.386	388.391	391.394	0	0	0	0	14.800	14.800	14.800	0.000	0.000	0.000
ATTACH 119	30168	37.750	17.062	-9.500	388.389	390.393	393.396	0	0	0	0	18.900	18.900	18.900	0.000	0.000	0.000
ATTACH 120	30169	37.750	-16.563	-9.500	391.392	393.396	396.399	0	0	0	0	4.700	4.700	4.700	0.000	0.000	0.000
ATTACH 121	2001	95.875	-97.875	-24.260	394.395	396.399	399.402	0	0	0	0	3.252	3.252	3.252	0.000	0.000	0.000
ATTACH 122	2005	50.750	-97.875	-24.260	397.398	399.402	402.405	0	0	0	0	5.920	5.920	5.920	0.000	0.000	0.000
ATTACH 123	2009	5.625	-97.875	-24.260	400.401	402.405	405.408	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 124	2012	76.250	-86.750	-24.260	403.404	405.408	408.411	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 125	2016	25.250	-86.750	-24.260	406.407	408.411	411.414	0	0	0	0	7.160	7.160	7.160	0.000	0.000	0.000
ATTACH 126	2019	95.875	-73.750	-24.260	409.409	411.414	414.417	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 127	2023	50.750	-73.750	-24.260	412.413	414.417	417.419	0	0	0	0	4.126	4.126	4.126	0.000	0.000	0.000
ATTACH 128	2027	5.625	-73.750	-24.260	415.416	417.419	420.422	0	0	0	0	7.343	7.343	7.343	0.000	0.000	0.000
ATTACH 129	2039	76.250	-50.750	-24.260	418.419	420.422	423.425	0	0	0	0	5.314	5.314	5.314	0.000	0.000	0.000
ATTACH 130	2042	25.250	-50.750	-24.260	421.422	423.425	426.428	0	0	0	0	3.208	3.208	3.208	0.000	0.000	0.000
ATTACH 131	2048	95.875	-42.375	-24.260	424.425	426.428	429.431	0	0	0	0	3.208	3.208	3.208	0.000	0.000	0.000
ATTACH 132	2053	50.750	-42.375	-24.260	427.428	429.431	432.434	0	0	0	0	4.476	4.476	4.476	1.000	1.000	1.000
ATTACH 133	2058	5.625	-42.375	-24.260	430.431	432.434	435.437	0	0	0	0	4.476	4.476	4.476	1.000	1.000	1.000
ATTACH 134	2060	56.890	-37.203	-24.260	433.434	435.437	438.440	0	0	0	0	4.071	4.071	4.071	1.000	1.000	1.000
ATTACH 135	2062	46.650	-37.203	-24.260	436.437	438.440	441.442	0	0	0	0	3.269	3.269	3.269	1.000	1.000	1.000
ATTACH 136	2071	56.000	-32.610	-24.440	439.440	441.442	444.445	0	0	0	0	4.200	4.200	4.200	0.000	0.000	0.000
ATTACH 137	2073	45.790	-32.610	-24.440	442.443	444.445	447.448	0	0	0	0	3.715	3.715	3.715	0.000	0.000	0.000
ATTACH 138	2074	50.750	-31.750	-13.920	445.446	447.448	450.451	0	0	0	0	4.757	4.757	4.757	0.000	0.000	0.000
ATTACH 139	2076	50.750	-27.820	-14.500	448.449	450.451	453.454	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 140	2101	95.875	-99.035	-24.034	451.452	453.454	456.458	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 141	2105	50.750	-99.035	-24.034	454.455	456.458	459.461	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 142	2109	5.625	-99.035	-24.034	457.458	459.461	462.464	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 143	2112	76.250	-109.350	-19.867	460.461	462.464	465.467	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 144	2116	25.250	-109.350	-19.867	463.464	465.467	468.469	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 145	2119	95.875	-126.040	-13.124	466.467	468.469	471.472	0	0	0	0	6.844	6.844	6.844	0.000	0.000	0.000
ATTACH 146	2123	50.750	-126.040	-13.124	469.470	471.472	474.475	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 147	2127	5.625	-126.040	-13.124	472.473	474.475	477.478	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 148	2130	76.250	-142.729	-6.381	475.476	477.478	480.481	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 149	2134	25.250	-142.729	-6.381	478.479	480.481	483.484	0	0	0	0	0.000	0.000	0.000	0.000	0.000	0.000
ATTACH 150	2137	95.875	-153.044	-2.214	481.482	483.484	486.487	0	0	0	0	4.186	4.186	4.186	0.000	0.000	0.000

Table 4.1-2 (Continued)

RUN NO. LSD900

DATE 070181
RUN BY T.E. POLLAK

ORIGINAL PAGE 15
OF POOR QUALITY

PHASE 3 JITTER ORBITAL MODEL																	
DYNAMIC MODEL SUMMARY TABLE																	
COORDINATES																	
DESC.	Stat. No.	Sub. No.	COORDINATES			DOF TABLE						WEIGHT DATA					
			X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
A	151	2141	50.750	-153.044	-2.214	472.473	474	0	0	0	0	3.398	3.398	1.923	0.	0.	0.
	152	2145	5.625	-153.044	-2.214	475.476	477	0	0	0	0	4.752	4.752	1.872	0.	0.	0.
	153	2201	95.875	-207.864	19.935	478.479	480	0	0	0	0	4.910	4.910	1.960	0.	0.	0.
	154	2205	50.750	-207.864	19.935	481.482	483	0	0	0	0	3.486	3.486	1.918	0.	0.	0.
	155	2209	5.625	-207.864	19.935	484.485	486	0	0	0	0	4.280	4.280	1.330	0.	0.	0.
	156	2212	76.250	-197.549	15.768	0	0	487	0	0	0	0.	0.	3.623	0.	0.	0.
	157	2216	25.250	-197.549	15.768	0	0	488	0	0	0	0.	0.	3.623	0.	0.	0.
	158	2219	95.875	-180.860	9.025	0	0	489	0	0	0	0.	0.	1.674	0.	0.	0.
	159	2223	50.750	-180.860	9.025	490.491	492	0	0	0	0	6.845	6.845	3.900	0.	0.	0.
	160	2227	5.625	-180.860	9.025	0	0	493	0	0	0	0.	0.	1.674	0.	0.	0.
B	161	2230	76.250	-164.171	2.282	0	0	494	0	0	0	0.	0.	3.377	0.	0.	0.
	162	2234	25.250	-164.171	2.282	0	0	495	0	0	0	0.	0.	3.405	0.	0.	0.
	163	2237	95.875	-153.856	-1.885	496.497	498	0	0	0	0	4.680	4.680	1.917	0.	0.	0.
	164	2241	50.750	-153.856	-1.885	499.500	501	0	0	0	0	3.358	3.358	1.919	0.	0.	0.
	165	2245	5.625	-153.856	-1.885	502.503	504	0	0	0	0	4.110	4.110	1.336	0.	0.	0.
	166	2301	5.625	-203.677	20.263	505.506	507	0	0	0	0	6.120	6.120	2.448	0.	0.	0.
	167	2305	5.625	-235.681	31.174	0	0	508	0	0	0	0.	0.	1.250	0.	0.	0.
	168	2309	5.625	-262.685	42.084	509.510	511	0	0	0	0	4.210	4.210	0.710	0.	0.	0.
	169	2339	25.250	-218.952	24.431	0	0	512	0	0	0	0.	0.	4.097	0.	0.	0.
	170	2343	25.250	-232.370	37.917	0	0	513	0	0	0	0.	0.	3.889	0.	0.	0.
C	171	2373	50.750	-208.677	20.263	514.515	516	0	0	0	0	2.963	2.963	1.800	0.	0.	0.
	172	2377	50.750	-235.681	31.174	517.518	519	0	0	0	0	4.973	4.973	3.132	0.	0.	0.
	173	2381	50.750	-262.685	42.084	520.521	522	0	0	0	0	2.963	2.963	1.800	0.	0.	0.
	174	2411	76.250	-218.952	24.431	0	0	523	0	0	0	0.	0.	4.168	0.	0.	0.
	175	2415	76.250	-252.370	37.917	0	0	524	0	0	0	0.	0.	3.889	0.	0.	0.
	176	2445	95.875	-208.677	20.263	525.526	527	0	0	0	0	6.120	6.120	2.448	0.	0.	0.
	177	2449	95.875	-235.681	31.174	0	0	528	0	0	0	0.	0.	1.250	0.	0.	0.
	178	2453	95.875	-262.685	42.084	529.530	531	0	0	0	0	4.210	4.210	0.710	0.	0.	0.
	179	2460	2.750	-213.549	22.232	532.533	534	535	536	537	0	1.816	1.816	1.816	1.00	1.00	1.00
	180	2461	98.750	-213.549	22.232	538.539	540	541	542	543	0	1.816	1.816	1.816	1.00	1.00	1.00
D	181	10272	42.300	0.	-117.380	544.545	546	547	548	549	0	14.073	14.073	14.073	516.00	516.00	80.00
	182	10273	42.300	0.	-123.380	550.551	552	553	554	555	0	12.815	12.815	12.815	355.00	355.00	73.00
	183	10500	42.300	0.	-25.150	556.557	558	559	560	561	0	12.477	12.477	12.477	160.00	160.00	160.00
	184	10501	42.300	0.	-54.450	562.563	564	0	0	0	0	13.140	13.140	13.140	0.	0.	0.
	185	10505	42.300	0.	-155.225	565.566	567	568	569	570	0	21.265	21.265	21.265	569.74	569.74	156.54
	186	10516	42.300	0.	-17.700	571.572	573	574	575	576	0	10.017	10.017	10.017	160.00	160.00	160.00
	187	10516	42.300	0.	-82.750	577.578	579	0	0	0	0	12.403	12.403	12.403	0.	0.	0.
	188	10517	42.300	24.000	-89.750	580.581	582	0	0	0	0	3.180	3.180	3.180	0.	0.	0.
	189	10519	46.350	0.	-54.450	582.584	585	0	0	0	0	0.160	0.160	0.160	0.	0.	0.
	190	10520	42.300	0.	-37.850	586.587	588	0	0	0	0	6.257	6.257	6.257	0.	0.	0.
E	191	10521	42.300	-4.960	-54.450	589.590	591	0	0	0	0	4.625	4.625	4.625	0.	0.	0.
	192	10522	42.300	4.960	-54.450	592.593	594	0	0	0	0	3.165	3.165	3.165	0.	0.	0.
	193	10570	39.050	7.750	-82.933	595.596	597	0	0	0	0	3.130	3.130	3.130	0.	0.	0.
	194	20001	32.550	-17.750	-167.139	598.599	600	0	0	0	0	3.460	3.460	3.460	0.	0.	0.
	195	20007	32.550	-17.750	-186.128	601.602	603	0	0	0	0	3.460	3.460	3.460	0.	0.	0.
	196	20018	42.300	-17.750	-177.427	604.605	608	0	0	0	0	29.230	29.230	29.230	0.	0.	0.
	197	20029	52.050	-17.750	-167.139	607.608	609	0	0	0	0	3.460	3.460	3.460	0.	0.	0.
	198	20035	52.050	-17.750	-186.127	610.611	612	0	0	0	0	4.080	4.080	4.080	0.	0.	0.
	199	20056	32.550	-9.500	-167.139	613.614	615	0	0	0	0	1.530	1.530	1.530	0.	0.	0.
	200	20061	32.550	-9.500	-183.028	616.617	618	0	0	0	0	6.020	6.020	6.020	0.	0.	0.

Table 4.1 (Continued)

RUN NO. LSD800

DATE 070181
RUN BY T.E. POLLAK

PHASE 3 JITTER ORBITAL MODEL
DYNAMIC MODEL SUMMARY TABLE
COORDINATES

DESC.	SAT NAME	SAT NO.	X	Y	Z	X	Y	Z	DOF TABLE RX RY RZ	WX	WY	WZ	WEIGHT DATA 1XX 1YY 1ZZ
201	20063		37 420	-9.500	-167.140	619 620 621	0 0 0	0	0	2.114	2.114	2.114	0. 0. 0.
202	20071		42 300	-9.500	-171.827	622 623 624	625 626 627	0	0	7.240	7.240	7.240	188.88 45.24 188.88
203	20073		42 300	-9.500	-177.427	628 629 630	0 0 0	0	0	6.000	6.000	6.000	0. 0. 0.
204	20084		52 050	-9.500	-167.139	631 632 633	0 0 0	0	0	1.920	1.920	1.920	0. 0. 0.
205	20099		42 300	-2.500	-177.427	634 635 636	0 0 0	0	0	7.110	7.110	7.110	0. 0. 0.
206	20119		52 050	6.500	-167.139	637 638 639	0 0 0	0	0	2.120	2.120	2.120	0. 0. 0.
207	20137		42 300	6.500	-177.427	640 641 642	0 0 0	0	0	5.690	5.690	5.690	0. 0. 0.
208	20141		37 420	6.500	-167.140	643 644 645	0 0 0	0	0	2.114	2.114	2.114	0. 0. 0.
209	20148		32 550	6.500	-167.139	646 647 648	0 0 0	0	0	1.530	1.530	1.530	0. 0. 0.
210	20153		32 550	6.500	-183.028	649 650 651	0 0 0	0	0	5.800	5.800	5.800	0. 0. 0.
211	20155		52 050	14.200	-167.139	652 653 654	0 0 0	0	0	4.280	4.280	4.280	0. 0. 0.
212	20161		52 050	14.200	-186.127	655 656 657	0 0 0	0	0	4.850	4.850	4.850	0. 0. 0.
213	20172		42 300	14.200	-177.427	658 659 660	0 0 0	0	0	9.360	9.360	9.360	0. 0. 0.
214	20183		32 550	14.200	-167.139	661 662 663	0 0 0	0	0	2.230	2.230	2.230	0. 0. 0.
215	20189		32 550	14.200	-186.128	664 665 666	0 0 0	0	0	2.230	2.230	2.230	0. 0. 0.
216	20191		30 279	-11.521	-186.127	667 668 669	670 671 672	0	0	1.340	1.340	1.340	1.00 1.00 1.00
217	20192		30 279	12.521	-186.127	673 674 675	676 677 678	0	0	1.340	1.340	1.340	1.00 1.00 1.00
218	20193		54 321	-11.521	-186.128	679 680 681	682 683 684	0	0	1.340	1.340	1.340	1.00 1.00 1.00
219	20194		54 321	12.521	-186.128	685 686 687	688 689 690	0	0	1.340	1.340	1.340	1.00 1.00 1.00
220	20198		42 300	0	-17.827	691 692 693	694 695 696	0	0	19.890	19.890	19.890	518.89 124.30 518.89
221	20509		42 300	-9.500	-54.450	697 698 699	0 0 0	0	0	2.210	2.210	2.210	0. 0. 0.
222	20512		42 300	6.500	-54.450	700 701 702	0 0 0	0	0	0.750	0.750	0.750	0. 0. 0.
223	1		51 235	2.894	-190.160	703 704 705	0 0 0	0	0	2.696	2.696	2.696	0. 0. 0.
224	2		33 365	-1.894	-190.160	706 707 708	0 0 0	0	0	2.696	2.696	2.696	0. 0. 0.
225	3		49 029	-24.614	-196.993	709 710 711	0 0 0	0	0	2.451	2.451	2.451	0. 0. 0.
226	4		35 571	25.614	-196.994	712 713 714	0 0 0	0	0	2.451	2.451	2.451	0. 0. 0.
227	5		63 607	28.267	-203.347	715 716 717	0 0 0	0	0	2.155	2.155	2.155	0. 0. 0.
228	6		20 993	-27.267	-203.347	718 719 720	0 0 0	0	0	2.155	2.155	2.155	0. 0. 0.
229	7		54 321	12.521	-191.037	721 722 723	0 0 0	0	0	0.837	0.837	0.837	0. 0. 0.
230	8		54 321	-11.521	-191.037	724 725 726	0 0 0	0	0	0.837	0.837	0.837	0. 0. 0.
231	9		30 279	-11.521	-191.036	727 728 729	0 0 0	0	0	0.837	0.837	0.837	0. 0. 0.
232	10		28 813	-9.849	-191.036	730 731 732	0 0 0	0	0	0.110	0.110	0.110	0. 0. 0.
233	11		30 254	12.521	-191.054	733 734 735	0 0 0	0	0	0.837	0.837	0.837	0. 0. 0.
234	12		54 821	12.521	-187.116	736 737 738	0 0 0	0	0	0.145	0.145	0.145	0. 0. 0.
235	13		54 321	12.521	-186.128	739 740 741	742 743 744	0	0	0.225	0.225	0.225	0.23 0.23 0.23
236	14		54 321	-11.521	-187.116	745 746 747	0 0 0	0	0	0.145	0.145	0.145	0. 0. 0.
237	15		54 321	-11.521	-186.128	748 749 750	751 752 753	0	0	0.225	0.225	0.225	0.23 0.23 0.23
238	16		30 279	-11.521	-187.116	754 755 756	0 0 0	0	0	0.145	0.145	0.145	0. 0. 0.
239	17		30 279	-11.521	-186.127	757 758 759	760 761 762	0	0	0.225	0.225	0.225	0.23 0.23 0.23
240	18		30 279	12.521	-187.116	763 764 765	0 0 0	0	0	0.145	0.145	0.145	0. 0. 0.
241	19		30 279	12.521	-186.127	766 767 768	769 770 771	0	0	0.225	0.225	0.225	0.23 0.23 0.23
242	20		47 293	5.493	-212.469	772 773 774	0 0 0	0	0	0.125	0.125	0.125	0. 0. 0.
243	21		47 293	-4.493	-212.469	775 776 777	0 0 0	0	0	0.125	0.125	0.125	0. 0. 0.
244	22		37 307	-4.493	-212.468	778 779 780	0 0 0	0	0	0.145	0.145	0.145	0. 0. 0.
245	23		37 307	5.493	-212.468	781 782 783	0 0 0	0	0	0.125	0.125	0.125	0. 0. 0.
246	24		43 184	-0.384	-212.469	784 785 786	0 0 0	0	0	0.040	0.040	0.040	0. 0. 0.
247	25		41 416	1.384	-212.458	787 788 789	0 0 0	0	0	0.040	0.040	0.040	0. 0. 0.
248	26		42 300	1.750	-212.469	790 791 792	0 0 0	0	0	0.140	0.140	0.140	0. 0. 0.
249	27		42 866	1.066	-212.459	793 794 795	0 0 0	0	0	0.345	0.345	0.345	0. 0. 0.
250	28		42 866	-0.066	-212.469	796 797 798	0 0 0	0	0	0.345	0.345	0.345	0. 0. 0.

Table 4.1-2 (Continued)

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. LSD900

DATE 070181
RUN BY T.E.POLLAK

PHASE 3 JITTER ORBITAL MODEL																	
DYNAMIC MODEL SUMMARY TABLE																	
COORDINATES																	
ESC.	Sub No.	No.	DOF TABLE									WEIGHT DATA					
			X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
251	29		41.735	-0.066	-212.469	709	800	801	0	0	0	0.345	0.345	0.345	0.	0.	0.
252	30		41.735	1.066	-212.469	802	803	804	0	0	0	0.345	0.345	0.345	0.	0.	0.
253	31		42.300	0.500	-208.324	805	806	807	0	0	0	0.120	0.120	0.120	0.	0.	0.
254	32		42.300	8.166	-211.117	808	809	810	0	0	0	0.066	0.066	0.066	0.	0.	0.
255	33		49.966	0.500	-211.117	811	812	813	0	0	0	0.066	0.066	0.066	0.	0.	0.
256	34		42.300	-7.166	-211.117	814	815	816	0	0	0	0.066	0.066	0.066	0.	0.	0.
257	35		34.634	0.500	-211.117	817	818	819	0	0	0	0.066	0.066	0.066	0.	0.	0.

Table 4.1-2 (Continued)

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.1-2 Deployed Solar Array Representation

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. DSAB1F

DATE 071381
RUN BY T.E.POLLAK

PHASE 3 JITTER ORBITAL MODEL
DSA FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
1	2001	95.875	-97.675	-24.260	1	2	3	0	0	0	4.700	4.700	1.338	0.	0.
2	2005	50.750	-97.875	-24.260	4	5	6	0	0	0	3.252	3.252	2.012	0.	0.
3	2009	5.625	-97.875	-24.260	7	8	9	0	0	0	5.920	5.920	2.548	0.	0.
4	2012	76.250	-86.750	-24.260	0	0	10	0	0	0	0.	4.140	0.	0.	0.
5	2016	25.250	-86.750	-24.260	0	0	11	0	0	0	0.	4.140	0.	0.	0.
6	2019	95.875	-74.250	-24.260	0	0	12	0	0	0	0.	1.885	0.	0.	0.
7	2023	50.750	-73.750	-24.260	13	14	15	0	0	0	7.160	7.160	3.896	0.	0.
8	2027	5.625	-74.250	-24.260	0	0	16	0	0	0	0.	1.885	0.	0.	0.
9	2039	76.250	-50.750	-24.260	0	0	17	0	0	0	0.	4.024	0.	0.	0.
10	2042	25.250	-50.750	-24.260	0	0	18	0	0	0	0.	4.024	0.	0.	0.
11	2048	95.875	-42.375	-24.260	19	20	21	0	0	0	4.126	4.126	0.860	0.	0.
12	2053	50.750	-42.375	-24.260	22	23	24	0	0	0	7.343	7.343	5.002	0.	0.
13	2058	5.625	-42.375	-24.260	25	26	27	0	0	0	5.314	5.314	2.051	0.	0.
14	2060	56.890	-37.203	-24.260	28	29	30	0	0	0	3.208	3.208	3.208	0.	0.
15	2062	46.650	-37.203	-24.260	31	32	33	0	0	0	3.208	3.208	3.208	0.	0.
16	2071	56.000	-32.610	-24.440	34	35	36	37	38	39	4.476	4.476	1.00	1.00	1.00
17	2073	45.790	-32.610	-24.440	40	41	42	43	44	45	4.476	4.476	1.00	1.00	1.00
18	2074	50.750	-31.750	-13.920	46	47	48	49	50	51	4.071	4.071	1.00	1.00	1.00
19	2076	50.750	-27.820	-14.500	52	53	54	55	56	57	3.269	3.269	1.00	1.00	1.00
20	2101	95.875	-99.035	-24.034	58	59	60	0	0	0	4.200	4.200	1.323	0.	0.
21	2105	50.750	-99.035	-24.034	61	62	63	0	0	0	3.715	3.715	2.238	0.	0.
22	2109	5.625	-99.035	-24.034	64	65	66	0	0	0	4.757	4.757	1.882	0.	0.
23	2112	76.250	-109.350	-19.867	0	0	67	0	0	0	0.	3.493	0.	0.	0.
24	2116	25.250	-109.350	-19.867	0	0	68	0	0	0	0.	3.522	0.	0.	0.
25	2119	95.875	-126.040	-13.124	0	0	69	0	0	0	0.	1.678	0.	0.	0.
26	2123	50.750	-126.040	-13.124	70	71	72	0	0	0	6.844	6.844	3.909	0.	0.
27	2127	5.625	-126.040	-13.124	0	0	73	0	0	0	0.	1.677	0.	0.	0.
28	2130	76.250	-142.729	-6.381	0	0	74	0	0	0	0.	3.493	0.	0.	0.
29	2134	25.250	-142.729	-6.381	0	0	75	0	0	0	0.	3.522	0.	0.	0.
30	2137	95.875	-153.044	-2.214	76	77	78	0	0	0	4.186	4.186	1.312	0.	0.
31	2141	50.750	-153.044	-2.214	79	80	81	0	0	0	3.998	3.998	1.923	0.	0.
32	2145	5.625	-153.044	-2.214	82	83	84	0	0	0	4.752	4.752	1.872	0.	0.
33	2201	95.875	-207.804	19.935	85	86	87	0	0	0	4.910	4.910	1.060	0.	0.
34	2205	50.750	-207.864	19.935	88	89	90	0	0	0	3.486	3.486	1.918	0.	0.
35	2209	5.625	-207.864	19.935	91	92	93	0	0	0	4.280	4.280	1.330	0.	0.
36	2212	76.250	-197.549	15.768	0	0	94	0	0	0	0.	3.623	0.	0.	0.
37	2216	25.250	-197.549	15.768	0	0	95	0	0	0	0.	3.623	0.	0.	0.
38	2219	95.875	-180.860	9.025	0	0	96	0	0	0	0.	1.674	0.	0.	0.
39	2223	50.750	-180.860	9.025	97	98	99	0	0	0	6.845	6.845	3.500	0.	0.
40	2227	5.625	-180.860	9.025	0	0	100	0	0	0	0.	1.674	0.	0.	0.
41	2230	76.250	-164.171	2.282	0	0	101	0	0	0	0.	3.377	0.	0.	0.
42	2234	25.250	-164.171	2.282	0	0	102	0	0	0	0.	3.405	0.	0.	0.
43	2237	95.875	-153.856	-1.885	103	104	105	0	0	0	4.680	4.680	1.917	0.	0.
44	2241	50.750	-153.856	-1.885	106	107	108	0	0	0	3.358	3.358	1.919	0.	0.
45	2245	5.625	-153.856	-1.885	109	110	111	0	0	0	4.110	4.110	1.336	0.	0.
46	2301	5.625	-208.677	20.263	112	113	114	0	0	0	6.120	6.120	2.448	0.	0.
47	2305	5.625	-235.677	31.174	0	0	115	0	0	0	0.	1.250	0.	0.	0.
48	2309	5.625	-262.677	42.084	116	117	118	0	0	0	4.210	4.210	0.710	0.	0.
49	2339	25.250	-218.992	24.431	0	0	119	0	0	0	0.	4.097	0.	0.	0.
50	2343	25.250	-252.370	37.917	0	0	120	0	0	0	0.	3.889	0.	0.	0.

Table 4.1-3

RUN NO. DSAB1F

DATE 071381
RUN BY T.E. POLLAK

PHASE 3 JITTER ORBITAL MODEL
OSA FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
51 2373	50.750	-208.677	20.263	121	122	123	0	0	0	2.963	2.963	1.800	0.	0.	0.
52 2377	50.750	-235.681	31.174	124	125	125	0	0	0	4.973	4.973	3.132	0.	0.	0.
53 2381	50.750	-262.685	42.084	127	128	129	0	0	0	2.963	2.963	1.800	0.	0.	0.
54 2411	76.250	-218.992	24.431	0	0	130	0	0	0	0.	0.	4.168	0.	0.	0.
55 2415	76.250	-252.370	37.917	0	0	131	0	0	0	0.	0.	2.889	0.	0.	0.
56 2445	95.875	-208.677	20.263	132	133	134	0	0	0	6.120	6.120	2.448	0.	0.	0.
57 2449	95.875	-235.681	31.174	0	0	135	0	0	0	0	0.	1.250	0	0.	0.
58 2453	95.875	-262.685	42.084	136	137	138	0	0	0	4.210	4.210	0.710	0.	0.	0.
59 2460	2.750	-213.549	22.232	139	140	141	142	143	144	1.816	1.816	1.816	1.00	1.00	1.00
60 2461	98.750	-213.549	22.232	145	146	147	148	149	150	1.816	1.816	1.816	1.00	1.00	1.00

Table 4.1-3 (Continued)

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

unit (SC-CU). A representation of the MMS structure is presented in Figure 4.1-3. A weight breakdown is shown in Table 4.1-4. A substructure DOF summary is presented in Table 4.1-5. An acceptable equilibrium check in the free-free configuration was used for model acceptance. Reference 3 describes the efforts of the Stress group in determining free-free acceptability.

The TDRSS boom assembly defined in the current model is a modal test verified structure incorporating all structural changes to reflect test correlation as presented in Reference 4. A representation of the boom structure is presented in Figure 4.1-4.

The TRW supplied RF Compartment NASTRAN model and SAP formulated Ku/S-Band Antenna model were those assembled in models LSD700 (Reference 5) and LSD801 (Reference 1). Gimbal drive assembly stiffness properties (tuned from modal test results) associated with the RF Compartment math model are presented in Table 4.1-6. Representations of the RF Compartment and Ku/S-Band substructures are presented in Figures 4.1-5 and 4.1-6. Respective boom/RF Compartment and Ku/S-Band Antenna substructure DOF summaries are shown in Tables 4.1-7 and 4.1-8.

The Instrument Module (IM) used for orbital model LSD900 is a completely revised model incorporating the numerous modifications to the free-free model as assembled in model LSD801. The previous free-free static model represented by 642 nodes and 3065 degrees-of-freedom is currently represented by 957 nodes and 5082 degrees-of-freedom. References 6 and 7 detail the modification analysis undertaken by the Stress Analysis Group to make the previous baseline IM reasonably compatible with the

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.1-4 Weight Breakdown For Updated MMS (Tuned)

<u>Component</u>	<u>Total Weight</u>	<u>Remarks</u>
ACS Module	345.38	
Power Module	503.6	Includes 3rd Battery
C and DH Module	250.67	Includes Tape Recorders
Propulsion Tank (PM1)	337.0	Includes Fuel + Pressurant
Propulsion Tank (PM1A)	400.2	Includes Fuel + Pressurant
Earth Sensor	26.00	
SC-CU	56.38	
PAF	150.77	Not in Free-Free Model
MSS	504.423	Includes Harness, Thermal Subsystem, Grapppler, Misc. Electrical, Propulsion Tank Support Structure

Total Substructure Wt. = 2574.423

2423.653 W/O PAF

RUN NO. MMS301

DATE 071301
RUN BY T.E.PILLAK

PHASE 3 JITTER ORBITAL MODEL
MMS FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
1	3000	-46.100	0.	0.	1	2	3	0	0	0	400.200	400.200	400.200	0.	0.
2	4600	-8.800	-25.981	-15.000	4	5	6	0	0	0	41.630	41.630	41.630	0.	0.
3	4650	-61.000	-25.981	-15.000	7	8	9	0	0	0	41.630	41.630	41.630	0.	0.
4	4682	-8.800	-21.075	-14.723	10	11	12	0	0	0	40.710	40.710	40.710	0.	0.
5	4692	-8.800	21.075	-14.723	13	14	15	0	0	0	40.710	40.710	40.710	0.	0.
6	4700	-8.800	25.981	-15.000	16	17	18	0	0	0	41.630	41.630	41.630	0.	0.
7	4750	-61.000	25.981	-15.000	19	20	21	0	0	0	41.630	41.630	41.630	0.	0.
8	4782	-8.800	23.288	-10.890	22	23	24	0	0	0	43.447	43.447	43.447	0.	0.
9	4792	-8.800	2.213	25.613	25	26	27	0	0	0	43.447	43.447	43.447	0.	0.
10	4800	-8.800	0.	30.000	28	29	30	0	0	0	41.630	41.630	41.630	0.	0.
11	4850	-61.000	0.	30.000	31	32	33	0	0	0	41.630	41.630	41.630	0.	0.
12	4875	-24.900	0.	37.050	34	35	36	37	38	39	56.380	56.380	3600.00	2000.00	2500.00
13	4876	-43.810	0.	37.800	40	41	42	43	44	45	26.000	26.000	500.00	400.00	400.00
14	4882	-8.800	-2.213	25.613	46	47	48	0	0	0	24.665	24.665	24.665	0.	0.
15	4892	-8.800	-23.288	-10.890	49	50	51	0	0	0	24.665	24.665	24.665	0.	0.
16	5709	-3.200	0.	30.000	52	53	54	0	0	0	12.333	12.333	12.333	0.	0.
17	5737	-3.200	-25.981	-15.000	55	56	57	0	0	0	12.333	12.333	12.333	0.	0.
18	5765	-3.200	25.981	-15.000	58	59	60	0	0	0	12.333	12.333	12.333	0.	0.
19	6200	-56.800	-23.000	-14.723	61	62	63	0	0	0	31.300	31.300	31.300	0.	0.
20	6208	-56.800	-23.000	-31.723	64	65	66	0	0	0	23.760	23.760	23.760	0.	0.
21	6228	-10.800	-23.000	-31.723	67	68	69	0	0	0	23.760	23.760	23.760	0.	0.
22	6316	-38.400	-13.800	-31.723	70	71	72	0	0	0	34.435	34.435	34.435	0.	0.
23	6320	-29.200	-13.800	-31.723	73	74	75	0	0	0	34.435	34.435	34.435	0.	0.
24	6616	-38.400	13.800	-31.723	76	77	78	0	0	0	34.435	34.435	34.435	0.	0.
25	6620	-29.200	13.800	-31.723	79	80	81	0	0	0	34.435	34.435	34.435	0.	0.
26	6700	-56.800	23.000	-14.723	82	83	84	0	0	0	31.300	31.300	31.300	0.	0.
27	6708	-56.800	23.000	-31.723	85	86	87	0	0	0	23.760	23.760	23.760	0.	0.
28	6728	-10.800	23.000	-31.723	88	89	90	0	0	0	23.760	23.760	23.760	0.	0.
29	6999	-33.800	3.000	-20.723	91	92	93	0	0	0	50.000	50.000	50.000	0.	0.
30	7200	-56.800	24.250	-12.557	94	95	96	0	0	0	34.547	34.547	34.547	0.	0.
31	7208	-56.800	38.972	-4.057	97	98	99	0	0	0	49.949	49.949	49.949	0.	0.
32	7228	-18.800	58.972	-4.057	100	101	102	0	0	0	6.591	6.591	6.591	0.	0.
33	7316	-38.400	34.372	3.910	103	104	105	0	0	0	128.046	128.046	128.046	0.	0.
34	7320	-29.200	34.372	3.910	106	107	108	0	0	0	27.663	27.663	27.663	0.	0.
35	7616	-38.400	20.572	27.812	109	110	111	0	0	0	146.583	146.583	146.583	0.	0.
36	7620	-29.200	20.572	27.812	112	113	114	0	0	0	19.772	19.772	19.772	0.	0.
37	7700	-56.800	1.250	27.280	115	116	117	0	0	0	34.547	34.547	34.547	0.	0.
38	7708	-56.800	15.972	35.780	118	119	120	0	0	0	46.682	46.682	46.682	0.	0.
39	7728	-10.800	15.972	35.780	121	122	123	0	0	0	9.220	9.220	9.220	0.	0.
40	8200	-56.800	-1.250	27.280	124	125	126	0	0	0	15.885	15.885	15.885	0.	0.
41	8208	-56.800	-15.972	35.780	127	128	129	0	0	0	13.681	13.681	13.681	0.	0.
42	8228	-10.800	-15.972	35.780	130	131	132	0	0	0	13.681	13.681	13.681	0.	0.
43	8316	-38.400	-20.572	27.812	133	134	135	0	0	0	41.044	41.044	41.044	0.	0.
44	8320	-29.200	-20.572	27.812	136	137	138	0	0	0	41.044	41.044	41.044	0.	0.
45	8616	-38.400	-34.372	3.910	139	140	141	0	0	0	41.044	41.044	41.044	0.	0.
46	8620	-29.200	-34.372	3.910	142	143	144	0	0	0	41.044	41.044	41.044	0.	0.
47	8700	-56.800	-24.250	-12.557	145	146	147	0	0	0	15.885	15.885	15.885	0.	0.
48	8708	-56.800	-38.972	-4.057	148	149	150	0	0	0	13.681	13.681	13.681	0.	0.
49	8728	-10.800	-38.972	-4.057	151	152	153	0	0	0	13.681	13.681	13.681	0.	0.
50	9000	-71.700	0.	0.	154	155	156	157	158	159	337.000	337.000	71170.00	45240.00	35290.00

Table 4.1-5

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY





Figure 4.1-4 Deployed TDRSS Boom Representation

Table 4.1-6 GDA Stiffness Properties for Orbital Model LSD900

GIMBAL DRIVE ASSEMBLY
LANDSAT D

ORIGINAL PAGE IS
OF POOR QUALITY



ELEVATION AXIS

$$\begin{aligned} E1/L &= 1.507 \times 10^6 \text{ LB-IN/RAD} \\ A1/L &= 2.314 \times 10^6 \text{ LB/IN} \\ A2/L &= .857 \times 10^6 \text{ LB/IN} \\ G1/L &= 1.15 \times 10^5 \text{ LB-IN/RAD} \end{aligned}$$

ROLL AXIS

$$\begin{aligned} E1/L &= 1.53 \times 10^6 \text{ LB-IN/RAD} \\ A1/L &= 1.35 \times 10^6 \text{ LB/IN} \\ A2/L &= 2.03 \times 10^6 \text{ LB/IN} \end{aligned}$$

PITCH AXIS

$$\begin{aligned} E1/L &= 12 \times 10^5 \text{ LB-IN/RAD} \\ A1/L &= 17.03 \times 10^6 \text{ LB/IN} \\ A2/L &= 6.5 \times 10^6 \text{ LB/IN} \end{aligned}$$

AZIMUTH AXIS (a0198-10505)

MASTRAN CDAR ELEMENT

$$\begin{aligned} \text{AREA} &= .730403 \\ I_1 &= .738394 \\ I_2 &= 1.10759 \\ J &= 0.175 \end{aligned}$$

NOTE: The overall torsional stiffness of each axis of the GDA will be revised by the incorporation of the spring constant of the harmonic drive in series with the other structural components shown above. The effective CDAR of the harmonic drive assemblies for each axis with tuning modifications incorporated is 25004 in-lb/rad for the elevation axis and 21025 in-lb/rad for the azimuth axis.

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.1-5 Deployed RF Compartment Representation

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.1-6 Deployed TRW Supplied Ku/S-Band Antenna

RUN NO. BRFT01

DATE 071381
RUN BY T E. POLLAK

PHASE 3 JITTER ORBITAL MODEL
BOOM/RFC FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
1 10272	42.300	0.	-117.380	1	2	3	4	5	6	14.073	14.073	14.073	516.00	516.00	80.00
2 10273	42.300	0.	-123.380	7	8	9	10	11	12	12.815	12.815	12.815	355.00	355.00	73.00
3 10500	42.300	0.	-25.150	13	14	15	16	17	18	12.477	12.477	12.477	160.00	160.00	160.00
4 10501	42.300	0.	-54.450	19	20	21	0	0	0	13.140	13.140	13.140	0.	0.	0.
5 10505	42.300	0.	-155.225	22	23	24	25	26	27	21.265	21.265	21.265	569.74	569.74	156.54
6 10515	42.300	0.	-17.700	28	29	30	31	32	33	10.017	10.017	10.017	160.00	160.00	160.00
7 10516	42.300	0.	-82.750	24	25	26	0	0	0	12.403	12.403	12.403	0.	0.	0.
8 10517	42.300	24.000	-89.750	37	38	39	0	0	0	3.180	3.180	3.180	0.	0.	0.
9 10519	46.350	0.	-54.450	40	41	42	0	0	0	0.160	0.160	0.160	0.	0.	0.
10 10520	42.300	0.	-27.850	43	44	45	0	0	0	6.257	6.257	6.257	0.	0.	0.
11 10521	42.300	-4.960	-54.450	46	47	48	0	0	0	4.625	4.625	4.625	0.	0.	0.
12 10522	42.300	4.960	-54.450	49	50	51	0	0	0	3.165	3.165	3.165	0.	0.	0.
13 10570	39.050	7.750	-82.933	52	53	54	0	0	0	3.130	3.130	3.130	0.	0.	0.
14 20001	32.550	-17.750	-167.139	55	56	57	0	0	0	3.460	3.460	3.460	0.	0.	0.
15 20007	32.550	-17.750	-186.128	58	59	60	0	0	0	3.460	3.460	3.460	0.	0.	0.
16 20018	42.300	-17.750	-177.427	61	62	63	0	0	0	29.230	29.230	29.230	0.	0.	0.
17 20029	52.050	-17.750	-167.139	64	65	66	0	0	0	3.460	3.460	3.460	0.	0.	0.
18 20035	52.050	-17.750	-186.127	67	68	69	0	0	0	4.080	4.080	4.080	0.	0.	0.
19 20056	32.550	-9.500	-167.139	70	71	72	0	0	0	1.530	1.530	1.530	0.	0.	0.
20 20061	32.550	-9.500	-183.028	73	74	75	0	0	0	6.020	6.020	6.020	0.	0.	0.
21 20063	37.420	-9.500	-167.140	76	77	78	0	0	0	2.114	2.114	2.114	0.	0.	0.
22 20071	42.300	-9.500	-171.827	79	80	81	82	83	84	7.240	7.240	7.240	188.88	45.24	188.88
23 20073	42.300	-9.500	-177.427	85	86	87	0	0	0	6.000	6.000	6.000	0.	0.	0.
24 20084	52.050	-9.500	-167.139	88	89	90	0	0	0	1.920	1.920	1.920	0.	0.	0.
25 20099	42.300	-2.500	-177.427	91	92	93	0	0	0	7.110	7.110	7.110	0.	0.	0.
26 20119	52.050	6.500	-167.139	94	95	96	0	0	0	2.120	2.120	2.120	0.	0.	0.
27 20137	42.300	6.500	-177.427	97	98	99	0	0	0	5.690	5.690	5.690	0.	0.	0.
28 20141	37.420	6.500	-167.140	100	101	102	0	0	0	2.114	2.114	2.114	0.	0.	0.
29 20148	32.550	6.500	-167.139	103	104	105	0	0	0	1.530	1.530	1.530	0.	0.	0.
30 20153	32.550	6.500	-183.028	106	107	108	0	0	0	5.800	5.800	5.800	0.	0.	0.
31 20155	52.050	14.200	-167.139	109	110	111	0	0	0	4.280	4.280	4.280	0.	0.	0.
32 20161	52.050	14.200	-186.127	112	113	114	0	0	0	4.850	4.850	4.850	0.	0.	0.
33 20172	42.300	14.200	-177.427	115	116	117	0	0	0	9.360	9.360	9.360	0.	0.	0.
34 20183	32.550	14.200	-167.139	118	119	120	0	0	0	2.230	2.230	2.230	0.	0.	0.
35 20189	32.550	14.200	-186.128	121	122	123	0	0	0	2.230	2.230	2.230	0.	0.	0.
36 20191	30.279	-11.521	-186.127	124	125	126	127	128	129	1.340	1.340	1.340	1.00	1.00	1.00
37 20192	30.279	12.521	-186.127	130	131	132	133	134	135	1.340	1.340	1.340	1.00	1.00	1.00
38 20193	54.321	-11.521	-186.128	136	137	138	139	140	141	1.340	1.340	1.340	1.00	1.00	1.00
39 20194	54.321	12.521	-186.128	142	143	144	145	146	147	1.340	1.340	1.340	1.00	1.00	1.00
40 20198	42.300	0.	-171.827	148	149	150	151	152	153	19.890	19.890	19.890	518.89	124.30	518.89
41 20509	42.300	-9.500	-54.450	154	155	156	0	0	0	2.210	2.210	2.210	0.	0.	0.
42 20512	42.300	6.500	-54.450	157	158	159	0	0	0	0.750	0.750	0.750	0.	0.	0.

Table 4.1-7

ORIGINAL PAGE IS
OF POOR QUALITY

R1W NO. KUANT2

DATE 071381
RUN BY T.E.POLLAKPHASE 3 JITTER ORBITAL MODEL
KU/S-BAND FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
1	1	51.235	2.894	-190.160	1	2	3	0	0	0	2.696	2.696	0.	0.	0.
2	2	33.365	-1.894	-190.160	4	5	6	0	0	0	2.696	2.696	0.	0.	0.
3	3	49.029	-24.614	-196.993	7	8	9	0	0	0	2.451	2.451	0.	0.	0.
4	4	35.571	25.614	-196.994	10	11	12	0	0	0	2.451	2.451	0.	0.	0.
5	5	63.607	28.267	-203.347	13	14	15	0	0	0	2.155	2.155	0.	0.	0.
6	6	20.993	-27.267	-203.347	16	17	18	0	0	0	2.155	2.155	0.	0.	0.
7	7	54.321	12.521	-191.037	19	20	21	0	0	0	0.837	0.837	0.	0.	0.
8	8	54.321	-11.521	-191.037	22	23	24	0	0	0	0.837	0.837	0.	0.	0.
9	9	30.279	-11.521	-191.036	25	26	27	0	0	0	0.837	0.837	0.	0.	0.
10	10	28.813	-9.844	-191.036	28	29	30	0	0	0	0.110	0.110	0.	0.	0.
11	11	30.254	12.521	-191.054	31	32	33	0	0	0	0.837	0.837	0.	0.	0.
12	12	54.321	12.521	-187.116	34	35	36	0	0	0	0.145	0.145	0.	0.	0.
13	13	54.321	12.521	-186.122	37	38	39	40	41	42	0.225	0.225	0.23	0.23	0.23
14	14	54.321	-11.521	-187.116	43	44	45	0	0	0	0.145	0.145	0.	0.	0.
15	15	54.321	-11.521	-186.128	46	47	48	49	50	51	0.225	0.225	0.23	0.23	0.23
16	16	30.279	-11.521	-187.116	52	53	54	0	0	0	0.145	0.145	0.	0.	0.
17	17	30.279	-11.521	-186.127	55	56	57	58	59	60	0.225	0.225	0.23	0.23	0.23
18	18	30.279	12.521	-187.116	61	62	63	0	0	0	0.145	0.145	0.	0.	0.
19	19	30.279	12.521	-186.127	64	65	66	67	68	69	0.225	0.225	0.23	0.23	0.23
20	20	47.293	5.493	-212.469	70	71	72	0	0	0	0.125	0.125	0.	0.	0.
21	21	47.293	-4.493	-212.469	73	74	75	0	0	0	0.125	0.125	0.	0.	0.
22	22	37.307	-4.493	-212.468	76	77	78	0	0	0	0.125	0.125	0.	0.	0.
23	23	37.307	5.493	-212.468	79	80	81	0	0	0	0.125	0.125	0.	0.	0.
24	24	43.184	-0.384	-212.469	82	83	84	0	0	0	0.040	0.040	0.	0.	0.
25	25	41.416	1.384	-212.468	85	86	87	0	0	0	0.040	0.040	0.	0.	0.
26	26	42.300	1.750	-212.469	88	89	90	0	0	0	0.140	0.140	0.	0.	0.
27	27	42.866	1.066	-212.469	91	92	93	0	0	0	0.345	0.345	0.	0.	0.
28	28	42.866	-0.066	-212.469	94	95	96	0	0	0	0.345	0.345	0.	0.	0.
29	29	41.735	-0.066	-212.469	97	98	99	0	0	0	0.345	0.345	0.	0.	0.
30	30	41.735	1.066	-212.469	100	101	102	0	0	0	0.345	0.345	0.	0.	0.
31	31	42.300	0.500	-208.324	103	104	105	0	0	0	0.120	0.120	0.	0.	0.
32	32	42.300	8.166	-211.117	106	107	108	0	0	0	0.066	0.066	0.	0.	0.
33	33	48.988	0.500	-211.117	109	110	111	0	0	0	0.066	0.066	0.	0.	0.
34	34	42.300	-7.166	-211.117	112	113	114	0	0	0	0.066	0.066	0.	0.	0.
35	35	34.634	0.500	-211.117	115	116	117	0	0	0	0.066	0.066	0.	0.	0.

Table 4.1-8

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

current design. References 8 thru 10 detail the analysis to update the design as shown on the released prints as of January 1981. The mission adapter is essentially the same as the previous model but updated to reflect the current configuration. The upper support structure represents a totally new model due to extensive differences between the old version and the current configuration. A major refinement to the previous model is the inclusion of a detailed SADAPTA simulation incorporating the bearing compliances of the SADAPTA shaft bearings. Another modification, found during the MTM vibration testing, was that the mono-ball bearings used at the ends of the 2.5 in. O.D. struts needed to be simulated. This simulation is included in the current substructure model. Two structural updates occurred in the TM area. First, the thematic mapper (TM) simulation was altered. Originally, the TM C.G. was modeled on a structurally tuned H-truss framework to insure a fundamental frequency of 100 Hz or greater. This simulation was modified to position the TM C.G. on a CBAR quadrupod (Q-pod) with element properties ensuring a fundamental frequency of greater than 250 Hz. Secondly, stiffnesses for the TM feet were included. Various TM foot NASTRAN models were generated by the stress group for this analysis and their results are presented in Reference 7. Table 4.1-9 presents the TM and TM foot simulation used in the current IM model. Improved support structure detail was incorporated into the baseline MSS experiment Q-pod simulation. The translational degrees-of-freedom at the four (4) attachment locations of the MSS Q-pod to the IM USS are still retained in the analysis set.

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.1-9 TM and TM Foot Simulation

TM C.G. Modeled On Q-Pod

CBEAM	1871	1124	1669	1670		
CBEAM	1872	1124	1669	1671		
CBEAM	1873	1124	1669	1672		
CBEAM	1874	1124	1669	1673		
PBEAM	1124	1004	0.80	945.0	945.	100.0
MAT1	1004	29.E+6	11.E+6	0.29		

TM Influence Foot Coefficients

CELAS1	41347	1	347	1	1671	1
CELAS1	42347	2	347	2	1671	2
CELAS1	43347	3	347	3	1671	3
CELAS1	41348	1	348	1	1672	1
CELAS1	42348	2	348	2	1672	2
CELAS1	43348	3	348	3	1672	3
CELAS1	41349	1	349	1	1673	1
CELAS1	42349	2	349	2	1673	2
CELAS1	43349	3	349	3	1673	3
CELAS1	41350	1	350	1	1674	1
CELAS1	42350	2	350	2	1674	2
CELAS1	43350	3	350	3	1674	3
PELAS	1		3225806.			
PELAS	2		729395.			
PELAS	3		729395.			

ORIGINAL PAGE IS
OF POOR QUALITY

To accurately define dynamic behavior, a detailed weight distribution was performed resulting in the current dynamic analysis set. Since this dynamic model incorporates in detail the changes associated with the previous free-free model (also used for modal tuning, Reference 11), a cross orthogonality check was performed between analytical and test data yielding acceptable results. This was the final step in substructure verification and led to its inclusion in the current analysis. Figure 4.1-7 shows a representation of the current IM structure with Table 4.1-10 defining the substructure DOF summary table. Table 4.1-11 presents a comparative summary of modeling revisions between models LSD801 and LSD900.

The detailed orbital model, LSD900, was assembled entirely on the VAX mini-computer using the SCAMP analysis code. Free-free MMS and IM substructures were coupled through the Triangular Transition Adapter (TTA). The TTA structure was represented by an updated (27x27) stiffness matrix derived from the simulation incorporated in the current MMS NASTRAN model. The RF Compartment is connected to the TDRSS boom through the azimuth drive and forms one complete NASTRAN assembly. The RF Compartment is rotated 90° CCW in VASTRAN from its modal test position (mounting feet along -X axis) to configure the structure in its worst case orbital mode. The Ku/S-Band Antenna was point-to-point coupled to the RFC at the four (4) attachment feet. This complete assemblage was in turn coupled to the MMS/IM using the fitting stiffness defined from the inner powered hinge to the IM attachment point. Lastly, the deployed solar array was attached to the MMS/IM at the SADAPTA interface using the aluminum jettison shaft from the SADAPTA to the jettison assembly apex as the

Figure 4.1-7 Updated Instrument Module Representation

ORIGINAL PAGE IS
OF POOR QUALITY

DATE 071381
RUN BY T.E.POLLAK

RUN NO. 1MB1FF

PHASE 3 JITTER ORBITAL MODEL
IM FREE-FREE DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	RX	RY	RZ	WX	WY	WZ	IXX	IYY	IZZ
1	320	8.000	3.821	29.204	1	2	3	0	0	0	25.313	25.313	0.	0.	0.
2	328	8.000	26.540	-10.390	4	5	6	0	0	0	17.125	17.125	0.	0.	0.
3	338	8.000	-26.540	-10.390	7	8	9	0	0	0	8.008	8.008	0.	0.	0.
4	346	8.000	-3.821	29.204	10	11	12	0	0	0	9.177	9.177	0.	0.	0.
5	347	8.000	7.524	20.380	13	14	15	0	0	0	1.650	1.650	0.	0.	0.
6	348	8.000	16.180	-3.550	16	17	18	0	0	0	1.680	1.680	0.	0.	0.
7	349	8.000	-4.820	-11.580	19	20	21	0	0	0	3.200	3.200	0.	0.	0.
8	350	8.000	-13.973	12.350	22	23	24	0	0	0	1.690	1.690	0.	0.	0.
9	420	0	3.821	29.204	25	26	27	0	0	0	23.123	23.123	0.	0.	0.
10	446	0.	-3.821	29.023	28	29	30	0	0	0	7.785	7.785	0.	0.	0.
11	460	0.	23.224	-17.820	31	32	33	0	0	0	10.886	10.886	0.	0.	0.
12	7.1	0	27.045	-11.202	34	35	36	0	0	0	13.653	13.653	0.	0.	0.
13	470	0	-23.224	-17.820	37	38	39	0	0	0	8.048	8.048	0.	0.	0.
14	471	0.	-27.045	-11.202	40	41	42	0	0	0	7.053	7.053	0.	0.	0.
15	1011	8.000	-21.000	-20.000	43	44	45	0	0	0	14.048	14.048	0.	0.	0.
16	1020	8.000	21.000	-20.000	46	47	48	0	0	0	12.593	12.593	0.	0.	0.
17	1034	15.250	-21.000	-20.000	49	50	51	0	0	0	11.426	11.426	0.	0.	0.
18	1043	19.250	21.000	-20.000	52	53	54	0	0	0	10.330	10.330	0.	0.	0.
19	1075	36.500	-21.000	-20.000	55	56	57	0	0	0	19.521	19.521	0.	0.	0.
20	1079	36.500	-5.500	-20.000	58	59	60	0	0	0	8.167	8.167	0.	0.	0.
21	1081	36.500	5.500	-20.000	61	62	63	0	0	0	7.194	7.194	0.	0.	0.
22	1085	33.500	21.000	-20.000	64	65	66	0	0	0	18.670	18.670	0.	0.	0.
23	1127	55.000	-21.000	-20.000	67	68	69	0	0	0	26.723	26.723	0.	0.	0.
24	1132	55.000	-5.500	-20.000	70	71	72	0	0	0	15.602	15.602	0.	0.	0.
25	1133	55.000	5.500	-20.000	73	74	75	0	0	0	19.651	19.651	0.	0.	0.
26	1136	55.000	21.000	-20.000	76	77	78	0	0	0	25.888	25.888	0.	0.	0.
27	1155	74.000	-11.000	-20.000	79	80	81	0	0	0	10.401	10.401	0.	0.	0.
28	1159	74.000	-5.500	-20.000	82	83	84	0	0	0	5.498	5.498	0.	0.	0.
29	1160	74.000	5.500	-20.000	85	86	87	0	0	0	13.359	13.359	0.	0.	0.
30	1163	74.000	21.000	-20.000	88	89	90	0	0	0	17.135	17.135	0.	0.	0.
31	1200	36.500	-21.000	-9.000	91	92	93	0	0	0	8.581	8.581	0.	0.	0.
32	1203	36.500	21.000	-9.000	94	95	96	0	0	0	10.535	10.535	0.	0.	0.
33	1269	55.000	-21.000	-9.000	97	98	99	0	0	0	17.738	17.738	0.	0.	0.
34	1279	55.000	21.000	-9.000	100	101	102	0	0	0	14.309	14.309	0.	0.	0.
35	1298	74.000	-21.000	-9.000	103	104	105	0	0	0	4.405	4.405	0.	0.	0.
36	1302	74.000	-5.500	-9.000	106	107	108	0	0	0	12.322	12.322	0.	0.	0.
37	1303	74.000	5.500	-9.000	109	110	111	0	0	0	12.322	12.322	0.	0.	0.
38	1303	74.000	21.000	-9.000	112	113	114	0	0	0	4.482	4.482	0.	0.	0.
39	1468	25.250	-18.000	-24.000	115	116	117	118	119	120	2.158	2.158	1.00	1.00	1.00
40	1469	25.250	18.000	-24.000	121	122	123	124	125	126	2.158	2.158	1.00	1.00	1.00
41	1482	76.250	-18.000	-24.000	127	128	129	130	131	132	2.023	2.023	1.00	1.00	1.00
42	1495	76.250	18.000	-24.000	133	134	135	136	137	138	2.023	2.023	1.00	1.00	1.00
43	1526	75.375	-11.215	-10.485	139	140	141	0	0	0	0.800	0.800	0.	0.	0.
44	1528	75.375	7.215	-10.485	142	143	144	0	0	0	0.800	0.800	0.	0.	0.
45	1529	75.375	-4.961	-21.250	145	146	147	0	0	0	2.235	2.235	0.	0.	0.
46	1530	75.375	4.960	-21.250	148	149	150	0	0	0	2.235	2.235	0.	0.	0.
47	1554	71.000	7.750	-5.000	151	152	153	0	0	0	2.528	2.528	0.	0.	0.
48	1555	60.500	7.750	-5.000	154	155	156	0	0	0	2.528	2.528	0.	0.	0.
49	1560	71.000	-6.250	-5.000	157	158	159	0	0	0	2.528	2.528	0.	0.	0.
50	1561	60.500	-6.250	-5.000	160	161	162	0	0	0	2.528	2.528	0.	0.	0.

Table -10

RUN NO. 1MB1FF

DATE 071381
RUN BY T.E.PCLLAK

PHASE 3 JITTER ORBITAL MODEL
IM FREE-JET DYNAMIC MODEL SUMMARY TABLE

	X	Y	Z	X	Y	Z	UX	UY	RZ	WX	WY	WZ	IXX	IYY	IZZ
51 1572	50 750	-21.000	-14.500	163 184	165 166	167 168	2.000	2.000	2.000	2.000	2.000	2.000	1.00	1.00	1.00
52 1621	53 920	-21.000	19.249	169 170	171 0	0 0	5.262	5.262	5.262	5.262	5.262	5.262	0	0	0
53 1633	53 920	21.000	19.249	172 173	174 0	0 0	6.415	6.415	6.415	6.415	6.415	6.415	0	0	0
54 1649	42 300	0	-16.500	175 176	177 178	179 180	22.629	22.629	22.629	22.629	22.629	22.629	44.00	44.00	44.00
55 1654	67.200	0	1.660	181 182	183 184	185 186	130.000	130.000	130.000	130.000	130.000	130.000	16181.00	7780.00	12724.00
56 1659	21.100	6.380	0.820	187 188	189 190	191 192	549.700	549.700	549.700	549.700	549.700	549.700	271300.00	95472.00	222617.00
57 1679	75.375	0	-16.250	193 194	195 0	0 0	2.971	2.971	2.971	2.971	2.971	2.971	0	0	0
58 30012	53.750	11.078	12.045	196 197	198 0	0 0	19.100	19.100	19.100	19.100	19.100	19.100	0	0	0
59 30014	53.750	-10.579	12.045	199 200	201 0	0 0	19.700	19.700	19.700	19.700	19.700	19.700	0	0	0
60 30019	53.750	11.078	25.465	202 203	204 0	0 0	3.935	3.935	3.935	3.935	3.935	3.935	0	0	0
61 30021	53.750	-10.579	25.465	205 206	207 0	0 0	3.300	3.300	3.300	3.300	3.300	3.300	0	0	0
62 30060	37.750	11.078	12.045	208 209	210 0	0 0	32.300	32.300	32.300	32.300	32.300	32.300	0	0	0
63 30064	37.750	-10.579	12.045	211 212	213 0	0 0	35.600	35.600	35.600	35.600	35.600	35.600	0	0	0
64 30077	37.750	11.078	25.465	214 215	216 0	0 0	3.635	3.635	3.635	3.635	3.635	3.635	0	0	0
65 30081	37.750	-10.579	25.465	217 218	219 0	0 0	3.000	3.000	3.000	3.000	3.000	3.000	0	0	0
66 30152	46.250	0.250	28.986	220 221	222 0	0 0	5.000	5.000	5.000	5.000	5.000	5.000	0	0	0
67 30166	53.750	17.062	-9.500	223 224	225 0	0 0	7.200	7.200	7.200	7.200	7.200	7.200	0	0	0
68 30167	53.750	-16.563	-9.500	226 227	228 0	0 0	10.400	10.400	10.400	10.400	10.400	10.400	0	0	0
69 30168	37.750	17.062	-9.500	229 230	231 0	0 0	14.800	14.800	14.800	14.800	14.800	14.800	0	0	0
70 30169	37.750	-16.563	-9.500	232 233	234 0	0 0	18.900	18.900	18.900	18.900	18.900	18.900	0	0	0

Table 4.1-10 (Continued)

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.1-11 Orbital Jitter Models Comparative Summary

ITEM	LSD801	LSD901
MMS	12/80 Updated Model From NASA-Goddard	06/81 Tuned Model From NASA-Goddard
MSS USS Grids In Aset	Yes	Yes
TDRSS Boom	Tuned Analytical Model	Modal Model With Re-Tuned 2nd Y-Bending Mode
Deployed Solar Array	NASTRAN Verified Modal Test Model	NASTRAN Verified Modal Test Model
Instrument Module	NASTRAN Verified Modal Test Model	Updated NASTRAN Verified Modal Test Model
Ku/S-Band Antenna	Modified Antenna With Feed Corrections	As Per LSD801
RF Compartment	Per TRW-99DOF/6DOF At Node 20071 Original Detailed Elevation Drive	As Per LSD801
GDA Stiffness Properties	TRW Beam Equivalent Properties For Azimuth Drive	Modification For Azimuth Drive
Total Number of Assembled Substructures	5	5
Total Nodal Locations	228	257
Total Dynamic Degrees-of- Freedom	723	819

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

coupling link. This shaft was tuned to represent the SADAPTA torsional stiffness of 30,000 in-lb/rad. Appendage coupling stiffness values are presented in Table 4.1-12.

4.2 TDRSS BOOM RE-TUNING

In the series of models associated with the previous orbital analysis, concern was expressed over the proximity of the TDRSS boom second Y-bending mode to the fundamental forcing harmonic of the MSS experiment at 13.62 Hz.

In the previous modal tuning effort, the 2nd boom Y-bending mode was tuned to a frequency of 13.407 Hz compared to the test validated frequency of 14.47. To effect a re-tuning of this mode, a parametric variation on the previously tuned modal test model (Reference 4) was performed. The shifted on-orbit 2nd Y-bending frequency to 14.142 Hz. better meets the test acceptance criteria for an analytical model.

All the NASTRAN model changes incorporated in re-tuning the analytical model are shown in Table 4.2-1. Using the changes shown, a new set of analytical frequencies and mode shapes was determined. A comparison of the measured test modes and the updated analytical modes is shown in Table 4.2-2.

The analytical model used for the re-tuning effort contained 306 degrees-of-freedom (DOF) including 54 DOF's on the suspension system. To estimate the effect of having a finite number of measurement points in the test set-up, the 306 DOF mode shapes were used to extract only

Table 4.1-12 Appendage Coupling Stiffnesses

DESCRIPTION	CONNECTION NODES	LENGTH	TORSION	STIFFNESS VALUES		
				BENDING	SHEAR	AXIAL
KU/S-BAND ANTENNA TO RF COMPARTMENT	13 TO 20194	0.0	185,000	26,000	185,000	26,000
	15 TO 20193					
	17 TO 20191					
	19 TO 20192					
KU/S-BAND ANTENNA - RF COMPARTMENT - TRUSS BOOM TO IM	1649 TO 10515	1.20 IN	103,720, 000	8,705, 400	134,770, 000	22,275,000
	1572 TO 2076					
DS/A TO IM		6.82 IN	30,000	181,030	3,085, 200	1,672,000

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.2-1 Changes For Pe-Tuning 2nd Y-Bending Mode Of Boom/RFC
NASTRAN Model

RELEASED HINGE JOINT FLEXIBILITY SIMULATION
TUNING OF TEST MEASURED MODES 1 AND 21

TEST	30000	50	42.30	0.0	-21.425	32	
TEST	20100	50	42.30	0.0	-21.425	52	
TEST	101	7500	10515	00000	1154		2
TEST	100	106172	80100	10500	10503		2
TEST	7500	501	2.75	15.9362	15.9562	31.9125	
TEST	106172	5023	3.7310	10.5510	10.5510	21.100	
TEST	500	80000	1	1.0	80100	1	-1.00
TEST	500	30000	3	1.0	80100	2	-1.00
TEST	500	60000	3	1.0	80100	3	-1.00
TEST	500	60000	6	1.0	80100	6	-1.00
TEST	50400	1.50E6	80000	4	40100	4	
TEST	50401	8.0E5	90000	5	80100	5	

RELEASED HINGE REVISIONS
TUNING OF TEST MEASURED MODE 61

TEST	100	10207	3	1.0	10204	3	-1.00
TEST	200	10208	3	1.0	10265	3	-1.00
TEST	110 07	110207	10207	3	10264	3	
TEST	110 07	110207	10205	1	10265	3	
TEST	110207	80312					

RELEASED HINGE REVISIONS
TUNING OF TEST MEASURED MODES 4 AND 71

TEST	25000	85000	20198	10535	10503		2	
TEST	85000	1201	.730483	.738394	738394	052522		+PBAR850
TEST	85000	1291	.730488	.738394	1.10759	1750		+PBAR850

ELEVATION RILE REVISIONS
TUNING OF TEST MEASURED MODE 31

TEST	26040	2.83E4	20195	5	20196	5	
TEST	26100	2.85E4	20197	5	20198	5	
TEST	26040	50197	20195	5	20196	5	
TEST	26100	50197	20197	5	20198	5	

Table 4.2-2 Comparison of Measured To Tuned NASTRAN Modal
Frequency Values

Mode Number	Measured Frequency (Hz)	Excitation Axis	Predicted Frequency (Hz)	Frequency Difference (%)
1	1.20	X	1.173	-2.25
2	1.23	Y	1.235	+0.407
3	2.72	SPS	2.806	+3.16
4	3.01	Y	2.968	-1.40
5	6.930	Y	7.416	+7.01
6	11.90	X	12.408	+4.27
7	14.47	Y	14.124	-2.39

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

the 42 modal amplitudes which were measured in the test. An orthogonality check was performed on this truncated mode set. The results of this check are shown in Table 4.2-3. The analytical tuned modes associated with this model are tabulated in Table 4.2-4 and shown in Figures 4.2-1 thru 4.2-7. A cross orthogonality check between the re-tuned analytical model and test data is presented in Table 4.2-5.

4.3 RESPONSE DATA

To aid ACS engineering in their simulation studies to determine orbital control responsiveness of the Landsat-D spacecraft, modal torque admittance data for various spacecraft nodal locations are provided. The nodes shown in Figure 4.1-1 and presented in Table 4.3-1 represent the locations for which data, thru 25 Hz, is to be supplied. Table 4.3-2 presents the structural transfer function coefficient data (Damping = 0.001) for the current orbital configuration model, LSD900. This data is also preserved on the following accessible dynamics data base permfile:

1R400492/TP/ORBIT/PICKOUT4/LS900ACS

Table 4.3-3 presents the coefficients to be used for an assumed damping of 0.01. This data is preserved on the following dynamics data base permfile:

1R400492/TP/ORBIT/PICKOUT4/LS901ACS

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.2-3

Self-Ortho Check Of Tuned Analytical
Model (306 DOF) Truncated To 42 DOF
Test Set

PHI(T) = M * PHI								
	1	2	3	4	5	6	7	
FREQ.	1 173	1 235	2 306	2 968	7 416	12 403	14 124	
DAMP.	0	0	0	0	0	0	0	
FREQ.								
1 1 173	1.000	0.001	0.000	0.002	0.000	-0.000	-0.001	
2 1 235	0.001	1.000	-0.003	-0.018	-0.001	-0.001	0.006	
3 2 306	0.000	-0.003	1.000	0.005	0.001	0.001	-0.001	
4 2 968	0.002	-0.018	0.005	1.000	-0.000	0.001	0.001	
5 7 416	0.000	-0.001	0.001	-0.000	1.000	0.000	-0.013	
6 12 403	-0.000	-0.001	0.001	0.001	0.000	1.000	0.000	
7 14 124	-0.001	0.006	-0.001	0.001	-0.013	0.000	1.000	

MODAL DOF PRODUCT MATRIX								
	1	2	3	4	5	6	7	
FREQ.	1 173	1 235	2 306	2 968	7 416	12 403	14 124	
DAMP.	0	0	0	0	0	0	0	
FREQ.								
1 1 173	1.000	0.001	0.002	0.000	0.004	-0.000	0.009	
2 1 235	0.001	1.000	0.005	0.004	-0.007	0.004	0.006	
3 2 306	0.002	0.005	1.000	0.013	-0.005	0.001	0.001	
4 2 968	0.000	0.004	0.013	1.000	0.003	0.004	0.019	
5 7 416	0.004	-0.007	-0.005	0.003	1.000	0.009	-0.002	
6 12 403	-0.000	0.004	0.001	0.004	0.009	1.000	0.010	
7 14 124	0.009	0.006	0.001	0.019	-0.002	0.010	1.000	

ORIGINAL PAGE IS
OF POOR QUALITY

Table 4.2-4 Re-Tuned TDRSS Boom Mode Identification

<u>Mode Number</u>	<u>Frequency</u>	<u>Description</u>
1	1.173	1st X-Bending
2	1.235	1st Y-Bending
3	2.806	Elevation Drive
4	2.968	Azimuth Drive
5	7.416	GDA Bending
6	12.408	2nd X-Bending
7	14.124	2nd Y-Bending

SD 5M MODAL MDL/ACC WTS • DEPR SUS
ID-DYDR-95 MM ANT-SUS • P-TUNED 2V

JULY 6 1961 • 3000CF • MODE NUMBER 1.000
ANALYTICAL MOD 5 FREQUENCY HZ: 1.173

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.2-1

LSD BM MODAL MOL/ACC W'S • PEPR 5.5
PED-OTDR-RF-MM ANT SUS • E-TUNED 2

JULY 6 1981 • 30500F • MODE NUMBER 2.000
-NAL TICAL MOD C FREQ.ENCY (HZ) 1.235

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.2-2

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.2-3

ORIGINAL PAGE 19
OF POOR QUALITY




Figure 4.2-4

LSD M SDAL L/ACC 4 S • DEPR SUS
PED+DOR-RE MM AN' • S • S • RE TUNED 2V

JULY 6 1961 • 30500F • CDE NUMBER 5-000
ANALYTICAL MODES FREQUENCY (HZ) .415

ORIGINAL PAGE 13
OF POOR QUALITY




Figure 4.2-5

1 BY MODAL ANALYSIS • SPR SUS
1-DTOR-REF-M ANT-SUS • PE TUNED 2V

JULY 6 1961 • 30500F • ODE NUMBER 6.000
ANALYTICAL ODES FREQUENCY (HZ) 12.400

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.2-6

1 BM MODAL MDL/ACC WTS • D PR SUS
1-D DR-RE MM ANT-SUS • RE-TUNED 2

JULY 6 1961 • 305DCP • MODE NUMBER 7.000
-NALYTICA MODES FREQUENCY (HZ) 14.12.

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 4.2-7

Table 4.2-5

Landsat-D Deployed TDRSS Boom Cross
Orthogonality Between Measured Modes And
Tuned Analytical Model

ORIGINAL PAGE IS
 OF POOR QUALITY

PHI(T) = M * PHI								
	1	2	3	4	5	6	7	
	X1.20H	Y1.23H	SPS2.7	Y3.01H	X6.93H	X11.9H	Y14.5H	
FREQ.	1.200	1.230	2.720	3.010	6.930	11.900	14.470	
DAMP.	0.094	0.033	0.090	0.033	0.011	0.071	0.012	
FREQ.								
1 1.173	0.933	-0.178	-0.053	-0.007	-0.019	-0.035	-0.089	
2 1.235	0.096	0.985	0.013	-0.025	0.106	-0.042	-0.025	
3 2.826	-0.109	-0.029	0.955	-0.176	0.005	0.038	-0.018	
4 2.969	0.019	-0.022	-0.247	-0.997	0.001	-0.025	0.025	
5 7.416	-0.035	0.004	-0.006	-0.010	-0.992	-0.000	0.067	
6 12.409	-0.015	-0.006	0.012	0.006	-0.010	-0.982	-0.004	
7 14.124	0.053	0.050	0.014	-0.010	-0.110	0.003	0.979	

MODAL DOT PRODUCT MATRIX								
	1	2	3	4	5	6	7	
	X1.20H	Y1.23H	SPS2.7	Y3.01H	X6.93H	X11.9H	Y14.5H	
FREQ.	1.200	1.230	2.720	3.010	6.930	11.900	14.470	
DAMP.	0.084	0.033	0.090	0.033	0.011	0.071	0.012	
FREQ.								
1 1.173	0.933	-0.151	0.019	-0.106	-0.010	0.037	-0.052	
2 1.235	0.136	0.990	0.023	-0.133	0.175	-0.034	0.083	
3 2.806	-0.077	-0.001	0.953	-0.176	0.079	0.048	0.016	
4 2.949	0.110	0.079	-0.254	-0.995	-0.101	-0.025	0.050	
5 7.416	-0.024	-0.021	-0.023	-0.095	-0.979	-0.025	0.013	
6 12.409	-0.013	0.004	0.031	-0.041	-0.025	-0.999	-0.003	
7 14.124	0.053	0.173	0.019	-0.022	-0.230	-0.007	0.954	

ORIGINAL PAGE 18
OF POOR QUALITY

Table 4.3-1 Representative Nodes in Data Transmittal To ACS

<u>Substructure Node Number</u>	<u>Description</u>	<u>Nodal* Degrees-of-Freedom</u>
9000	PM1 Propulsion Tank	6
1572	C/B Side of DS/A Shaft	6
1669	TM C.G.	6
1664	MSS C.G.	6
2076	DS/A Side of DS/A Shaft	6
2460	Sun Sensor (-X)	6
2461	Sun Sensor (+X)	6
20194	Ku/S-Band +X, +Y Mounting Foot	6
20198	Azimuth Drive Attachment To Elevation Drive	6

Total DOF: 54

*Structural transfer coefficient data for
rotational DOFS only are supplied to ACS
engineering.

RUN NO. LSD900

DATE 072081
RUN BY T.E.POLLAK

LSD PHASE 3 ORBITAL JITTER MODEL LSD900 * ALL TUNED * 819 DOOF'S
TRANSFER COEFFICIENTS * 9000-1572-1664-1669-2076-2460-2461-20194-20198

TABLE 4-3-2 STRUCTURAL TRANSFER
FUNCTION COEFFICIENT
VALUES FOR ORBITAL

MODEL LSD900.

DAMPING = 0.001

Modes

J	FREQ (HZ)	DAMPING C/CRIT	BJ	CJ
1	0.0053	0.0010	6.70674E-05	1.12451E-03
2	0.0169	0.0010	2.12761E-04	1.13168E-02
3	0.0177	0.0010	2.21853E-04	1.23047E-02
4	0.0256	0.0010	3.21890E-04	2.59018E-02
5	0.0304	0.0010	3.82176E-04	3.65146E-02
6	0.0504	0.0010	6.32912E-04	1.00145E-01
7	0.4279	0.0010	5.37752E-03	7.22944E-00
8	0.7627	0.0010	9.58475E-03	2.29669E-01
9	1.2091	0.0010	1.51935E-02	5.77106E-01
10	1.3212	0.0010	1.66022E-02	6.89081E-01
11	1.6147	0.0010	2.02908E-02	1.02929E-02
12	2.1454	0.0010	2.69595E-02	1.81703E-02
13	2.8692	0.0010	3.60558E-02	3.25006E-02
14	3.0802	0.0010	3.87072E-02	3.74562E-02
15	3.2717	0.0010	4.11139E-02	4.22588E-02
16	4.1520	0.0010	5.21763E-02	6.80592E-02
17	6.4704	0.0010	8.13101E-02	1.65283E-03
18	6.9147	0.0010	8.68925E-02	1.88758E-03
19	7.3855	0.0010	9.28093E-02	2.15339E-03
20	10.8891	0.0010	1.36837E-01	4.68107E-03
21	11.3794	0.0010	1.42938E-01	5.11211E-03
22	12.6360	0.0010	1.58789E-01	6.30351E-03
23	12.7815	0.0010	1.60617E-01	6.44948E-03
24	14.0760	0.0010	1.76884E-01	7.82202E-03
25	14.1420	0.0010	1.77719E-01	7.89556E-03
26	14.9920	0.0010	1.88395E-01	8.87319E-03
27	16.7710	0.0010	2.10751E-01	1.11040E-04
28	18.1626	0.0010	2.28238E-01	1.30232E-04
29	19.4022	0.0010	2.43815E-01	1.48615E-04
30	20.0658	0.0010	2.52155E-01	1.58956E-04
31	21.1241	0.0010	2.65454E-01	1.76165E-04
32	22.3963	0.0010	2.94008E-01	2.16101E-04
33	23.5055	0.0010	2.95380E-01	2.18123E-04
34	24.2761	0.0010	3.05064E-01	2.32660E-04
35	25.0166	0.0010	3.14369E-01	2.47070E-04

ORIGINAL PAGE IS
OF POOR QUALITY

Modes 1-6 Are Rigid Body Modes

DATE 072081
RUN BY T.E. POLLAK

LSD PHASE 3 ORBITAL JITTER MODEL LSD900 • ALL TUNED • 819 DOOF'S
 TRANSFER COEFFICIENTS • 9000-1572-1664-1669-2076-2460-2461-20194-20198

ORIGINAL PAGE IS
OF POOR QUALITY

[illegible]

Table 4.3-2 (Continued)

MODAL DIMENSIONS ARE IN THE INCH-POUND-SECOND SYSTEM

RUN NO. LSD900

DATE 072081
RUN BY T.E. POLLAK

LSD PHASE 3 ORBITAL JITTER MODEL LSD900 • ALL TUNED • 819 DDOF'S
TRANSFER COEFFICIENTS • 9000-1572-1664-1669-2076-2460-2461-20194-20198

TM C.G.			SHAFT			SUN SENSOR (-X)		
MODE	#1669	#1669	#2076	#2076	#2460	#2460	#2460	#2460
	THETA X	THETA Y	THETA Z	THETA X	THETA Y	THETA Z	THETA X	THETA Z
1	3.71440E-05	-2.88435E-03	-4.06397E-03	3.71675E-05	2.88402E-03	-4.06384E-03	3.72933E-05	-2.88386E-03
2	3.65704E-03	2.59987E-03	-2.31467E-03	3.65562E-03	2.60035E-03	-2.31417E-03	3.63808E-03	2.60031E-03
3	-1.50608E-03	1.98927E-03	-2.49725E-03	-1.50662E-03	1.98770E-03	-2.49833E-03	-1.51203E-03	1.98694E-03
4	4.82675E-04	1.95151E-05	-6.13870E-04	4.83722E-04	1.77898E-05	-6.14855E-04	4.89131E-04	1.68142E-05
5	-3.76598E-03	2.44198E-03	-2.09879E-03	-3.76363E-03	2.43924E-03	-2.10623E-03	-3.73159E-03	2.43779E-03
6	1.62781E-03	-5.54598E-05	-1.24703E-03	1.61981E-03	-4.52569E-05	-1.24148E-03	1.51847E-03	-4.07366E-05
7	3.15774E-03	4.26333E-04	-7.81371E-04	1.60892E-03	2.28906E-04	-1.00066E-03	-2.33077E-02	-7.28502E-04
8	9.12050E-04	-4.27673E-04	-2.70599E-03	7.45303E-04	2.28526E-02	1.27888E-03	-2.83632E-03	3.63888E-02
9	2.84630E-04	-3.48853E-03	-1.08959E-03	-3.33866E-04	1.03840E-02	3.16538E-03	6.33782E-03	-1.76890E-02
10	8.55193E-04	-1.75906E-03	2.23571E-03	1.24315E-03	1.94502E-02	-7.50693E-03	2.94852E-03	4.27158E-02
11	3.43518E-03	-1.20172E-03	2.59037E-04	9.47030E-03	9.38500E-04	-4.41346E-04	-4.50305E-02	2.81301E-03
12	2.92835E-03	-1.68182E-04	9.57139E-05	-2.65116E-03	-9.13094E-06	5.09059E-05	3.50131E-02	-1.07411E-03
13	2.28030E-04	-1.94019E-05	4.32438E-04	3.31493E-04	-1.96064E-03	2.66704E-04	3.42823E-04	1.93284E-03
14	-2.98364E-06	-2.15608E-04	5.20653E-04	4.17029E-05	5.77526E-02	-7.67624E-03	2.12792E-02	-4.21996E-02
15	2.25496E-04	-6.77660E-04	-3.57263E-05	2.95010E-05	3.01990E-03	-5.60327E-04	1.78636E-04	-2.14990E-03
16	-2.63246E-03	-4.82073E-04	-4.34158E-04	1.70761E-02	3.04609E-03	-3.47504E-04	5.40893E-02	4.21072E-03
17	1.60389E-03	-1.36844E-04	1.85616E-04	3.26104E-03	3.52242E-05	-2.43688E-05	3.29571E-03	1.70891E-04
18	1.53937E-03	2.53565E-04	4.75720E-04	1.83576E-04	-2.23161E-02	4.08163E-04	1.40633E-02	-2.23550E-03
19	3.09004E-05	5.40866E-05	-4.66762E-05	-7.65031E-04	-6.08362E-02	-1.42322E-03	9.11085E-02	-1.13629E-02
20	5.18807E-04	1.37427E-04	1.83576E-04	-1.90808E-04	1.15756E-02	1.63760E-03	6.45994E-03	6.66549E-03
21	3.69193E-05	1.70329E-05	-4.88921E-06	-9.23320E-04	7.29335E-02	7.36704E-03	9.31550E-02	3.86863E-02
22	3.49134E-05	-6.40331E-05	-6.15557E-05	-2.66358E-04	3.71594E-04	1.50146E-03	7.30960E-05	2.02848E-03
23	2.90229E-05	-2.94878E-05	1.26868E-04	-8.23040E-04	-3.54977E-03	4.82925E-04	2.40983E-02	-2.53473E-01
24	9.50961E-04	-2.82520E-04	-2.35636E-04	-2.32259E-02	6.24851E-02	1.01813E-02	-5.52933E-03	-2.50323E-02
25	-6.34156E-04	1.05977E-03	1.79059E-04	-1.24193E-02	4.20367E-02	6.42615E-03	-4.11926E-03	-1.30088E-02
26	4.01527E-04	-2.59788E-04	1.19399E-05	2.74032E-02	4.03703E-02	4.61094E-03	-2.03807E-02	-4.94149E-02
27	8.20742E-04	-1.44444E-03	-8.81653E-04	-6.09539E-02	-7.08109E-02	-4.65225E-03	-4.95881E-03	8.66559E-03
28	-2.31322E-04	-5.87525E-03	5.14996E-04	-2.04158E-02	-1.40593E-02	-3.36992E-02	-2.54018E-03	6.67817E-03
29	-1.66671E-05	1.22582E-04	9.78413E-04	8.36509E-03	9.28657E-03	-4.14286E-04	-6.53595E-02	4.29303E-02
30	-5.80142E-04	5.25002E-04	-6.03295E-03	4.80170E-02	2.98837E-03	2.70354E-03	-1.42920E-02	-2.05429E-03
31	5.63305E-04	-1.64461E-04	-1.21874E-04	-5.77836E-02	1.12431E-01	-9.95374E-03	3.31273E-03	8.15103E-03
32	4.24167E-04	-9.07099E-04	-2.81798E-03	6.35420E-04	1.1585E-04	-1.84924E-04	-1.93106E-02	-2.53839E-02
33	-1.09830E-05	-3.33557E-05	-5.29909E-04	9.28882E-03	-1.45963E-02	3.30144E-03	1.08137E-01	1.45387E-01
34	-2.51708E-04	-4.69646E-04	-1.09526E-03	4.81904E-02	7.54133E-02	-1.74726E-02	1.30661E-02	4.73848E-03
35	-2.03372E-04	-2.43853E-03	-3.33482E-03	1.18458E-02	5.10627E-03	-1.65123E-03	2.60184E-03	3.64147E-03

Table 4.3-2 (Continued)

* METAL DIMENSIONS ARE IN THE INCH-ROUND-SECOND SYSTEM

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO LSD900

DATE 072081
RUN BY T.E. POLLAK

LSD PHASE 3 ORBITAL JITTER MODEL LSD900 • ALL TUNED • 819 DOOF'S
TRANSFER COEFFICIENTS • 9000-1572-1664-1669-2076-2460-2461-20194-20198

SUN SENSOR (+X)			KV/S-BAND +X+Y ATTACHMENT			A2 DRIVE ATTACHMENT To EL DRIVE		
* #2461	#2461	#2461	#20194	#20194	#20194	#20198	#20198	#20198
MODE	THETA X	THETA Y	THETA Z	THETA X	THETA Y	THETA Z	THETA X	THETA Z
1	3 72952E-05	-2 88386E-03	-4 06382E-03	3 71963E-05	-2 88407E-03	-4 06398E-02	3 71887E-05	-2 88418E-03
2	3 72952E-05	-2 88386E-03	-4 06382E-03	3 65571E-03	-2 88407E-03	-4 06398E-02	3 65571E-03	-2 88407E-03
3	-1 51195E-03	1 98704E-03	-2 49866E-03	-1 50721E-03	1 99144E-03	-2 49754E-03	-1 50716E-03	1 99065E-03
4	-4 89118E-04	1 68952E-05	-6 15090E-04	-4 82908E-04	2 08239E-05	-6 14123E-04	-4 82937E-04	2 03856E-05
5	-3 73176E-03	2 43718E-03	-2 10456E-04	-3 76123E-03	2 43806E-03	-2 09714E-04	-3 76158E-03	2 43959E-03
6	1 51831E-03	-3 89637E-05	-1 24048E-03	1 62563E-03	-5 95732E-05	-1 24593E-04	1 62574E-03	-5 83172E-05
7	-2 33188E-02	-2 37028E-04	-1 11990E-03	3 94362E-03	6 55836E-04	-8 79449E-04	3 89581E-03	5 76569E-04
8	-1 19681E-03	3 64866E-02	1 26850E-04	1 00863E-03	-1 18031E-03	-2 81497E-07	9 94345E-04	-8 59034E-04
9	3 85578E-03	-1 78798E-02	6 86494E-03	9 80145E-04	1 97577E-02	-4 33353E-03	9 10095E-04	9 64464E-03
10	1 01502E-02	4 24540E-02	-1 74655E-02	8 54236E-05	9 34777E-03	1 30090E-03	2 96830E-05	4 32447E-03
11	-4 39911E-02	5 10944E-03	-2 15003E-03	-8 33861E-03	4 48829E-03	8 05171E-04	-7 49038E-03	1 51321E-03
12	-3 48589E-02	1 41261E-03	-5 65708E-04	-1 27150E-02	-5 65944E-04	-3 25336E-02	1 08866E-02	1 33333E-04
13	2 06839E-03	1 79169E-03	-1 23222E-03	-1 38531E-03	-2 93673E-02	-9 84608E-02	-1 16376E-03	-1 85777E-03
14	-2 43510E-02	-4 23188E-02	2 82526E-02	-5 55031E-04	5 54418E-03	-4 86782E-03	-4 30762E-04	3 42042E-04
15	-2 34331E-03	-2 03736E-03	1 28498E-03	1 71250E-03	-1 18261E-01	2 69360E-02	6 18924E-04	-7 32324E-04
16	5 28288E-02	-3 91417E-03	2 05005E-03	4 52180E-03	-8 11859E-04	1 12043E-03	3 09332E-03	3 00809E-04
17	-4 67526E-03	-7 02599E-04	2 75605E-04	8 26483E-02	9 72067E-03	1 66871E-04	3 60508E-02	5 94777E-04
18	2 45511E-02	4 84908E-03	-2 15207E-03	1 13249E-02	1 60380E-03	-1 83211E-04	4 34121E-03	-1 09946E-04
19	-8 95282E-02	-1 05521E-02	4 85753E-04	-2 84420E-06	1 70587E-04	-3 35775E-05	2 69886E-05	-1 79240E-04
20	-2 70022E-02	7 24744E-01	-5 60215E-03	4 30834E-04	2 26774E-04	-5 69198E-05	-3 07108E-05	-2 94038E-04
21	-8 59615E-02	5 61056E-02	-2 34965E-02	-3 38993E-05	-1 54853E-04	4 11635E-05	-2 05620E-05	3 18037E-04
22	-6 47773E-05	-2 05645E-03	6 96661E-04	2 53034E-03	3 22251E-02	-9 31220E-03	1 03825E-03	-8 00501E-02
23	3 09562E-02	2 49014E-01	-9 78162E-02	5 44618E-04	2 70240E-04	-8 20748E-05	3 93771E-04	-6 13274E-04
24	1 82533E-02	-3 58543E-02	1 12766E-02	-2 18055E-02	-7 73899E-04	4 56266E-04	2 39756E-02	2 64096E-04
25	1 01820E-02	-2 56121E-02	8 34933E-03	3 55791E-02	7 90581E-04	-4 38785E-04	-3 97055E-02	9 57440E-04
26	-1 72112E-02	2 59665E-02	-1 35725E-02	-9 71730E-04	1 07733E-04	-2 1858E-05	1 27127E-03	-4 57204E-04
27	3 24301E-03	1 07498E-02	-4 34887E-03	1 04507E-03	-6 43315E-04	8 68366E-05	-3 70230E-03	1 10949E-03
28	-8 34238E-04	-3 67622E-03	1 13491E-03	5 81945E-03	3 50909E-03	-4 05003E-04	4 52324E-03	-1 39106E-03
29	-7 07418E-03	-4 28795E-02	1 97578E-02	-1 02653E-03	-9 07458E-05	2 43786E-05	1 83763E-03	-1 96412E-04
30	-1 81057E-02	1 13511E-03	-1 43396E-03	3 77947E-03	-4 84040E-04	-5 03671E-05	-1 19999E-02	1 11252E-03
31	5 19559E-03	-2 07279E-02	1 73022E-02	4 36098E-04	-1 35568E-06	-2 24890E-05	-2 01758E-03	-3 44353E-04
32	-1 97109E-02	2 52692E-01	-1 01523E-02	4 36719E-04	3 28047E-04	-6 28666E-05	-7 71075E-04	-1 17254E-03
33	1 03410E-01	-1 43485E-01	5 55999E-02	-1 97307E-05	-1 52959E-04	2 01866E-06	1 1346E-03	-7 95740E-05
34	4 10423E-02	-1 59349E-02	1 52939E-02	1 26168E-04	3 02418E-04	-1 97859E-05	-8 495E-03	-1 29441E-05
35	5 24511E-03	-4 64200E-03	2 51270E-03	1 03728E-03	-1 62854E-03	-0 06762E-04	-1 5182E-03	-1 71905E-03

Table 4.3-2 (Continued)

* METRIC DIMENSIONS ARE IN THE INCH-POUND - GRAVITY SYSTEM

RUN NO LSD900

DATE 072381
RUN BY T E. POLLAK

LSD PHASE 3 ORBITAL JITTER MODEL LSD900 • ALL TUNED • 819 DOOF'S
TRANSFER COEFFICIENTS • 9000-1572-1664-16C9-2076-2460-2461-20194-20198

TABLE 4.3-3. STRUCTURAL TRANSFER

FUNCTION COEFFICIENT

VALUES FOR ORBITAL

Model LSD900

DAMPING=0.01

ORIGINAL PAGE 18
OF POOR QUALITY

Modes J	FREQ (HZ)	DAMPING C/CRIT	BJ	CJ
1	0.0053	0.0100	6.70574E-04	1.12451E-03
2	0.0169	0.0100	2.12761E-03	1.13168E-02
3	0.0177	0.0100	2.21853E-03	1.23047E-02
4	0.0256	0.0100	3.21880E-03	2.59018E-02
5	0.0304	0.0100	3.82176E-03	3.65146E-02
6	0.0504	0.0100	6.32912E-03	1.00145E-01
7	0.4279	0.0100	5.37752E-02	7.22944E 00
8	0.7627	0.0100	9.58475E-02	2.29669E 01
9	1.2091	0.0100	1.51935E-01	5.77106E 01
10	1.3212	0.0100	1.66022E-01	6.89081E 01
11	1.6147	0.0100	2.02908E-01	1.02929E 02
12	2.1454	0.0100	2.69595E-01	1.81703E 02
13	2.8692	0.0100	3.60558E-01	3.25006E 02
14	3.0802	0.0100	3.87072E-01	3.74562E 02
15	3.2717	0.0100	4.11139E-01	4.22588E 02
16	4.1520	0.0100	5.21763E-01	6.80592E 02
17	6.4704	0.0100	8.13101E-01	1.65283E 03
18	6.9147	0.0100	8.68925E-01	1.88758E 03
19	7.3855	0.0100	9.28093E-01	2.15339E 03
20	10.8891	0.0100	1.26827E 00	4.68107E 03
21	11.9794	0.0100	1.42898E 00	5.11311E 03
22	12.6360	0.0100	1.58789E 00	6.30351E 03
23	12.7815	0.0100	1.60617E 00	6.44948E 03
24	14.0760	0.0100	1.76884E 00	7.82202E 03
25	14.1420	0.0100	1.77714E 00	7.89556E 03
26	14.9920	0.0100	1.88395E 00	8.87319E 03
27	16.7710	0.0100	2.10751E 00	1.11040E 04
28	18.1626	0.0100	2.28238E 00	1.30232E 04
29	19.4022	0.0100	2.43815E 00	1.48615E 04
30	20.0658	0.0100	2.52155E 00	1.58956E 04
31	21.1241	0.0100	2.65454E 00	1.76165E 04
32	23.3963	0.0100	2.94008E 00	2.16101E 04
33	23.5055	0.0100	2.95380E 00	2.18123E 04
34	24.2761	0.0100	3.05064E 00	2.32660E 04
35	25.0166	0.0100	3.14369E 00	2.47070E 04

ORIGINAL PAGE IS
OF POOR QUALITY

As refinements occur in the current orbital stack-up, except for parametric variations and study models, the data base files will be updated and applicable documentation released.

5.0 ORBITAL ANALYSIS

5.1 ORBITAL ANALYSIS APPROACH

Since TM image data correction through real time analysis of component orbital jitter will be accomplished by the ADS, the primary focal point of this analysis is still MSS induced jitter as a function of the MSS component itself or the TM. TM peak responses, however, were noted throughout the analysis and as shown in subsequent data summary tables, are well within the control range of the ADS.

In addition to generating baseline jitter values, worst case variations of the eigenvalue spectrum were generated and the corresponding MSS/TM responses computed. This approach sought to identify the effect of possible structural frequency deviations from the best estimate by modifying the modal spectrum so that the maximum resonant response would be excited. Modes near each forcing harmonic which differed in frequency by more than 15% were not considered in the analysis. Shifts were implemented for the first seven harmonics in the Fourier representation of the MSS experiment and the first nine harmonics of the TM. The shift value for a particular mode was applied only to that modal frequency. The bandwidths investigated are presented in Figure 5.1-1. For example, the 68.10 Hz MSS third harmonic has bandwidth limits of 59.217 Hz and 80.118 Hz as prescribed by the 15% tolerance premise. The modal spectrum for model LSD900 reveals 26 modes within this allowable 15% bandwidth. Each mode was then individually shifted to become coincident with the

ORIGINAL PAGE IS
OF POOR QUALITY

Figure 5.1-1 MSS/TM Bandwidth Considerations

Bandwidth = +15%

Component = MSS

Harmonic	Frequency (Hz)	Lower Limit (Hz)	Upper Limit (Hz)	Force Coefficient
1	13.62	11.843	16.024	40.398
2	40.86	35.530	48.071	39.507
3	68.10	59.217	80.118	37.770
4	95.34	82.904	112.165	35.269
5	122.58	106.591	144.212	32.122
6	149.82	130.278	176.259	28.476
7	177.06	153.965	208.306	24.494

Bandwidth = +15%

Component - TM

Harmonic	Frequency (Hz)	Lower Limit (Hz)	Upper Limit (Hz)	Force Coefficient
1	7.0	6.087	8.235	43.343
2	21.0	18.261	24.706	41.543
3	35.0	30.435	41.176	38.106
4	49.0	42.609	57.647	33.341
5	63.0	54.783	74.118	27.663
6	77.0	66.957	90.588	21.547
7	91.0	79.130	107.059	15.476
8	105.0	91.304	123.529	9.8845
9	119.0	103.478	140.00	5.12

ORIGINAL PAGE IS
OF POOR QUALITY

68.10 Hz forcing function frequency. From a steady state response analysis on the altered modal spectrum, force coefficients for each forcing harmonic were obtained. The time-phased coefficients were then combined to produce a set of jitter values. The offensive mode(s) in that particular harmonic were identified by noting which responses exceeded the allotted jitter budget.

5.2 BASELINE ORBITAL MODEL - LSD900

The model presented herein incorporates all the revisions described in Sections 4.1 and 4.2. Table 5.2-1 describes the first twenty (20) elastic modes of the model with Figures 5.2-1 thru 5.2-20 presenting the corresponding modal plots. Table 5.2-2 tabularizes representative force/response locations for the frequency response spectra graphs ($C/C_{CRIT} = 0.001$) presented herein, Figures 5.2-21 thru 5.2-32. For an assumed 1% damping ($C/C_{CRIT} = 0.01$), Table 5.2-3 tabularizes representative force/response locations for the frequency response spectra graphs presented in Figures 5.2-33 thru 5.2-44. As depicted in Figures 5.2-27, 5.2-28 and 5.2-39, 5.2-40, resonant frequency placement precludes coincidence with the odd harmonic forcing stimulus of the MSS experiment. Worst case modal spectrum shifts, however, introduce jitter magnitudes in exceedance of MSS allowables. These established allowables are presented in Table 5.2-4. Tables 5.2-5 thru 5.2-11 present the results of TM and MSS single mode shift comparisons to MSS RMS allowables. Included are values for 15%-10%-5% bandwidth spreads about the forcing harmonic. If a particular data set is omitted then no worst cases appear in that

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-1 LS/D Final Tuned Orbital Model For Jitter - LSD900

<u>Mode Number</u>	<u>Frequency (Hz)</u>	<u>Description</u>
1-6	0.0	Rigid Body
7	0.428	1st Solar Array Pending
8	0.763	1st Solar Array Torsion
9	1.209	1st Boom X-Bending
10	1.321	2nd Solar Array Torsion
11	1.615	2nd Solar Array Bending + Boom Y
12	2.145	MMS ACS Module + S/A Bending
13	2.869	Elevation Drive
14	3.080	Solar Array 2nd Torsion
15	3.272	Azimuth Drive
16	4.152	Solar Array 3rd Bending
17	6.470	GDA Bending
18	6.915	Solar Array 4th Bending
19	7.386	Solar Array 3rd Torsion
20	10.889	Solar Array 3rd - 4th Panel Modes
21	11.379	Solar Array 4th Torsion
22	12.636	2nd Boom X-Bending
23	12.781	Solar Array Outboard Bending
24	14.076	Solar Array 5th Torsion + Inboard Local
25	14.142	2nd Boom Y-Bending
26	14.992	Solar Array 2nd-3rd Panel Bending

PHASE 3 ORBITAL MODEL LS0900
159-14254-00A150-800 RF159-KUS.17

ALL TUNED SUBS
/PRM/D13613

MODE NUMBER 7.000
FREQUENCY (HZ) 0.426

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-1

BASE 3 ORBITAL MODEL LSD000
9-14234-05A150-900000153-KUS:17

ALL TUNED SUBS
/PRM/D10613

MODE NUMBER 5.000
FREQUENCY (HZ) 0.753

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-2

PHASE 3 ORBITAL MODEL LSC900
79-1M234-25A150-900MRF153-KUS117

ALL TUNED SUBC
/PRM/D10613

MODE NUMBER 9.000
FREQUENCY (HZ) 1.203

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-3

PHASE 3 ORBITAL MODEL LSD900
159-14234-05A:50-8004RF159-KUS:17

ALL TUNED SUBS
/PRM/D10E13

MODE NUMBER 10.000
FREQUENCY (HZ) 1.321

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-4

PHASE 3 ORBITAL MODEL LSC000
159-14234-05A150-800MRF159-KUS117

ALL TUNED SUBS
/PRM/D10613

MODE NUMBER 11.000
FREQUENCY (HZ) 1.515

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-5

D PHASE 3 ORBITAL MODEL LSD300
S153-14234-DS150-500MRF159-KUG117

ALL TUNED SUBS
/PRM/D10613

MODE NUMBER 12.000
FREQUENCY (HZ) 2.145

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 3.2-6

D PHASE 3 ORBITAL MODEL L50900
S 53 1M234 05A150 800MR153 KUS117

ALL TUNED SUBS
/PRM/D10613

MODE NUMBER 13.000
FREQUENCY (HZ) 2.653

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-7

D PHASE 3 ORBITAL MODEL LSD300
S153-14234-05A150-80349-153-KUS117

ALL TUNED SUBS
/PR4/D10613

MODE NUMBER 14.000
FREQUENCY (HZ) 3 060

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-3

SD PHASE 3 OR L'AL MODEL LSD900
170159-1M234-05A150-90049F150-KUS117

ALL TUNED SUBS
/PRM/C10613

MODE NUMBER 15 000
FREQUENCY (HZ) 3.272




Figure 5.2-9

PHASE 3 ORBITAL MODEL LSDJCC
159-17234-05A150-5004RF153-KUS117

ALL TUNED SUBS
/PRM/D10513

MODE NUMBER 15.000
FREQUENCY (HZ) 4.152




Figure 5.2-10

SD 3-5 3 ORBITAL CD-FL LSD900
MC 3-14234-05A150-B004RF159-KUS117

-LL TUN D SUBS
/PRM/010513

U 11.000
R. UENCY H21 1.4 0

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-11

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-12

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-13

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-14

ORIGINAL PAGE IS
OF POOR QUALITY

The drawing is a detailed technical sketch of a mechanical assembly, likely a turbine or engine component. It features a large, complex structure on the left with multiple internal components and a large circular flange at the top right. The drawing is heavily annotated with 'X' marks, arrows, and other symbols, indicating specific points of interest or assembly details. The overall quality of the drawing is poor, with many lines and symbols appearing as noise or artifacts, suggesting it is a low-quality reproduction of an original document.

5-13

PH-SE 3 ORBITAL MODEL LSD300
59-14234-05A150-800MRF153-KUS117

ALL TUNED SUBS
/PRM/D13613

MODE NUMBER 22.000
FREQUENCY (HZ) 12.939

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-16




Figure 5.2-17

PHASE 3 ORBITAL MODEL LSD300
S153-14234-05A150-9004RF153-KUS117

ALL TUNED S BS
/PRM 010513

MODE NUMBER 24.000
FREQUENCY (HZ) 14.075

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-13

PHASE 3 ORBITAL MODEL LSD000
39-14234-05A150-9304RF159-KUS117

ALL TUNED SUBS
.PRM/D10613

MODE NUMBER 25 000
FREQUENCY (HZ) 14.142

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-19

3 PHASE 3 ORBITAL MODEL LSC000
5.53-14234-004150-80000015-KUG117

ALL TUNED SUBS
/PRM/D10613

MODE NUMBER 29 000
FREQUENCY (HZ) 14 392

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-20

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-2 LSD900 Transfer Function Data Presentation

Damping = 0.001

Excitation Grid Point	Response Grid Point	Response Spectrum Graph to 100 Hz	Response Spectrum Graph 100-200 Hz
TM θ_x #1669	MSS θ_x	5.1-21	5.1-22
	θ_y	5.1-23	5.1-24
	θ_z	5.1-25	5.1-26
MSS θ_x #1664	MSS θ_x	5.1-27	5.1-28
	θ_y	5.1-29	5.1-30
	θ_z	5.1-31	5.1-32

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA X
 DAMPING=0.001





Figure 5.2-21

ORIGINAL PAGE IS
 OF POOR QUALITY


LA, DSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA X
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-22


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Y
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-23


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Y
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-24

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Z
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-25

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Z
 DAMPING=0.001





Figure 5.2-26


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AND RESPONSE AT MSS THETA X
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-27

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AND RESPONSE AT MSS THETA X
 DAMPING=0.001



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-28

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
FORCE AT MSS THETA X - RESPONSE AT MSS THETA Y
DAMPING=0.001




Figure 5.2-29

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
FORCE AT MSS THETA X - RESPONSE AT MSS THETA Y
DAMPING=0.001




Figure 5.2-30

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT MSS THETA X - RESPONSE AT MSS THETA Z
 DAMPING=0.001




Figure 5.2-31

ORIGINAL PAGE IS
 OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.2-32


Table 5.2-3 LSD900 Transfer Function Data Presentation

Damping = 0.01

Excitation Grid Point	Response Grid Point	Response Spectrum Graph to 100 Hz	Response Spectrum Graph 100-200 Hz
TM θ_x #1669	MSS θ_x	5.1-33	5.1-34
	θ_y	5.1-35	5.1-36
	θ_z	5.1-37	5.1-38
MSS θ_x #1664	MSS θ_x	5.1-39	5.1-40
	θ_y	5.1-41	5.1-42
	θ_z	5.1-43	5.1-44

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA X
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-33

ORIGINAL PAGE 13
OF POOR QUALITY





Figure 5.2-34


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Y
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-35

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT TM THETA X - RESPONSE AT MSS THETA Y
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-36

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
FORCE AT TM THETA X - RESPONSE AT MSS THETA Z
DAMPING=0.01




Figure 5.2-37

ORIGINAL PAGE IS
OF POOR QUALITY





Figure 5.2-38


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AND RESPONSE AT MSS THETA X
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-39


LANDSAT D FINAL TUNED ORBITAL MODEL *** LSDJ00
 FORCE AND RESPONSE AT MSS THETA X
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-46

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT MSS THETA X - RESPONSE AT MSS THETA Y
 DAMPING=0.01



ORIGINAL PAGE IS
 OF POOR QUALITY

Figure 5.2-41

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
FORCE AT MSS THETA X - RESPONSE AT MSS THETA Y
DAMPING=0.01




Figure 5.2-42

ORIGINAL PAGE IS
OF POOR QUALITY

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
FORCE AT MSS THETA X - RESPONSE AT MSS THETA Z
DAMPING=0.01




Figure 5.2-43

LANDSAT D FINAL TUNED ORBITAL MODEL *** LSD900
 FORCE AT MSS THETA X - RESPONSE AT MSS THETA Z
 DAMPING=0.01




Figure 5.2-44

ORIGINAL PAGE 19
 OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-4 Jitter Allowables

<u>Experiment</u>	<u>Axis</u>	<u>RMS Allowables (Arc-Sec)</u>		
		<u>.30 Pixel</u>	<u>.40 Pixel</u>	<u>.50 Pixel</u>
MSS	θ_X	1.50	3.14	4.42
	θ_Y	1.3	3.0	4.3
	θ_Z	8.2	10.8	12.3
TM*	θ_X	20.0	-	-
	θ_Y	3.6	-	-
	θ_Z	6.0	-	-

*Values For TM Experiment Are Expressed
in Peak Arc-Sec.

RUN NO. ORB900

Model Number

DATE 072381
RUN BY T.E. POLLAK

Bandwidth

PRCERR=15 ZG=0.001 Damping

Forcing Location

JITTER MODEL LSD900
TM FORCES MSS/RMS ALLOWABLES

Response Location/Type Response

COEFF MODE	FCPS	RATIO	PATM	PSTM	PGTM	R4TM	R5TM	RGTM	PMSS	PMSS	PMSS	R4MSS	RMSS	RMSS
1 17	7.00	1.0818	5.95	0.76	0.88	4.29	0.41	0.51	2.24	0.97	1.53	1.51	0.44	1.01
1 18	7.00	1.0123	5.38	1.21	1.83	3.90	0.67	1.20	2.69	1.37	2.00	1.75	0.70	1.34
2 30	21.00	1.0466	1.39	0.40	1.02	0.85	0.21	0.62	4.29	0.68	0.82	2.31	0.38	0.49
3 41	35.00	1.0641	3.23	1.03	3.06	1.79	0.58	2.08	4.95	0.63	2.20	2.99	0.38	1.47
3 44	35.00	1.0157	1.41	0.76	0.33	0.85	0.41	0.17	1.22	2.40	0.25	0.72	1.66	0.12
3 50	35.00	0.9153	2.21	1.78	4.46	1.18	1.10	3.06	7.72	2.48	0.64	1.37	1.69	0.32
4 67	49.00	1.0087	9.68	2.17	3.15	6.12	1.44	2.09	3.53	1.47	3.00	1.89	0.81	2.01
4 76	49.00	0.8952	6.63	5.74	1.72	3.99	3.97	1.14	1.50	2.96	0.72	0.80	1.78	0.40

SHIFT VALUE TO HAVE MODAL
F_n = HARMONIC F_n

HARMONIC FREQUENCY

Mode No.

HARMONIC

ORIGINAL
OF PCOR

PAGE 13
QUALITY

TM RESPONSE
AMPLITUDES

MSS RESPONSE
AMPLITUDES

NOMENCLATURE:

P5.MSS

TYPE OF RESPONSE

P= PEAK
R= RMS

LOCATION OF RESPONSE

DIRECTION

4= Θx
5= Θy
6= Θz

Table 5.2-5

RUN NO. 0RB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL L50900 PRCERR=107 ZG=.001
TM FORCES MSS/RMS ALLOWABLES

COEFF	MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	RAMSS	R5MSS	R6MSS
1	17	7.00	1.0812	5.95	0.76	0.88	4.29	0.41	0.51	2.24	0.97	1.53	1.51	0.44	1.01
1	18	7.00	1.0123	5.38	1.21	1.83	3.90	0.67	1.20	2.69	1.37	2.00	1.75	0.70	1.34
2	30	21.00	1.0466	1.39	0.40	1.02	0.85	0.21	0.62	4.29	0.68	0.82	2.31	0.38	0.49
3	41	35.00	1.0641	3.23	1.03	3.06	1.79	0.58	2.08	4.95	0.63	2.20	2.99	0.38	1.47
3	44	35.00	1.0157	1.41	0.76	0.33	0.85	0.41	0.17	1.22	2.40	0.25	0.72	1.66	0.12
3	50	35.00	0.9153	2.21	1.78	4.46	1.18	1.10	3.06	2.72	2.48	0.64	1.37	1.69	0.32
4	67	49.00	1.0087	9.68	2.17	3.15	6.12	1.44	2.09	3.33	1.47	3.00	1.89	0.81	2.01

Table 5.2-6

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. ORB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL LSD900 PRCERR=5 ZG=.001
TM FORCES MSS/RMS ALLOWABLES

COEFF MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
1 18	7.00	1.0123	5.38	1.21	1.83	3.90	0.67	1.20	2.69	1.37	2.00	1.75	0.70	1.34
2 30	21.00	1.0466	1.39	0.40	1.02	0.85	0.21	0.62	4.29	0.68	0.82	2.31	0.38	0.49
3 44	35.00	1.0157	1.41	0.76	0.33	0.85	0.41	0.17	1.22	2.40	0.25	0.72	1.66	0.12
4 67	49.00	1.0087	9.68	2.17	3.15	6.12	1.44	2.09	3.33	1.47	3.00	1.89	0.81	2.01

Table 5.2-7

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. 0RB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL LSD900 PRCERR=15 ZG=.001
MSS FORCES MSS/RMS ALLOWABLES

COEFF	MODE	FCPS	RATIO	P4TH	P5TH	P6TH	R4TH	R5TH	R6TH	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
1	24	13.62	0.9676	1.75	0.63	0.58	1.16	0.36	0.37	6.57	0.51	1.11	3.80	0.26	0.71
1	25	13.62	0.9631	1.09	1.63	0.48	0.69	1.13	0.30	5.45	1.23	0.98	3.02	0.74	0.62
2	48	40.86	1.1091	0.84	3.58	2.85	0.43	2.48	1.89	6.25	2.57	2.79	3.89	1.61	1.87
2	49	40.86	1.0700	1.92	1.62	5.17	0.88	1.09	3.52	4.90	2.35	0.65	2.79	1.49	0.38
2	50	40.86	1.0686	1.63	1.86	5.22	0.96	1.27	3.56	3.51	2.84	0.69	1.83	1.83	0.41
2	64	40.86	0.8987	1.99	0.99	1.90	1.22	0.66	1.23	4.58	1.74	3.00	2.65	1.06	2.02
3	99	68.10	0.9613	0.37	0.37	0.49	0.19	0.19	0.24	2.60	6.17	0.38	1.25	4.23	0.18
3	102	68.10	0.9289	0.95	0.32	0.49	0.50	0.16	0.24	5.87	2.70	0.63	3.08	1.78	0.29
3	104	68.10	0.8981	0.58	0.73	0.74	0.28	0.43	0.38	3.69	0.28	0.47	1.73	0.16	0.21
3	105	68.10	0.8891	1.25	6.62	4.13	0.68	4.59	2.72	94.55	5.71	7.92	65.54	3.90	5.38
3	106	68.10	0.8845	0.53	1.98	2.48	0.23	1.31	1.56	15.67	1.41	1.05	9.86	0.88	0.56
3	107	68.10	0.8788	1.12	2.91	1.77	0.62	1.97	1.96	7.31	1.57	0.58	4.03	0.97	0.26
3	108	68.10	0.8674	3.15	6.05	4.75	2.04	4.19	3.15	46.86	10.75	1.26	31.85	7.43	0.70
3	109	68.10	0.8507	0.38	0.23	0.82	0.46	0.10	0.13	14.74	4.41	0.54	9.20	2.76	0.24
4	126	95.34	0.9572	0.75	0.70	0.95	0.41	0.36	0.46	3.51	0.37	2.90	1.59	0.19	1.94
4	127	95.34	0.9441	0.80	0.79	0.77	0.44	0.42	0.35	3.46	0.53	2.54	1.53	0.29	1.68
5	145	122.58	0.9127	0.88	1.01	0.84	0.45	0.62	0.39	5.53	8.30	0.77	2.72	5.63	0.40
5	147	122.58	0.8978	0.75	0.65	0.77	0.37	0.37	0.36	4.85	7.77	0.44	2.29	5.27	0.21
6	145	149.82	1.1156	0.66	0.65	0.68	0.30	0.37	0.30	4.03	4.96	0.61	1.88	3.33	0.27
6	147	149.82	1.0973	0.59	0.45	0.65	0.26	0.24	0.28	3.64	4.78	0.42	1.66	3.15	0.18

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-8

RUN NO. 0RB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL LSD900 PRCERR=10 ZG=.001
MSS FORCES MSS/RMS ALLOWABLES

COEFF	MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
1	24	13.62	0.9676	1.75	0.63	0.58	1.16	0.36	0.37	6.57	0.51	1.11	3.80	0.26	0.71
1	25	13.62	0.9631	1.09	1.63	0.48	0.69	1.13	0.30	5.45	1.23	0.98	3.02	0.74	0.62
2	43	40.86	1.0700	1.52	1.62	5.17	0.88	1.09	3.52	4.80	2.35	0.65	2.79	1.19	0.38
2	50	40.86	1.0686	1.63	1.86	5.22	0.96	1.27	3.56	3.51	2.84	0.69	1.83	1.83	0.41
3	99	68.10	0.9613	0.37	0.37	0.49	0.19	0.19	0.24	2.60	6.17	0.38	1.25	4.23	0.18
3	102	68.10	0.9289	0.95	0.32	0.49	0.50	0.16	0.24	5.87	2.70	0.63	3.08	1.78	0.29
4	126	95.34	0.9572	0.75	0.70	0.95	0.41	0.36	0.46	3.58	0.37	2.90	1.59	0.16	1.94
4	127	95.34	0.9441	0.80	0.79	0.77	0.44	0.42	0.35	3.46	0.53	2.54	1.53	0.29	1.68
5	145	122.58	0.9127	0.88	1.01	0.84	0.45	0.62	0.39	5.53	8.30	0.77	2.72	5.63	0.40
6	147	149.82	1.0973	0.59	0.45	0.65	0.26	0.24	0.28	3.64	4.78	0.42	1.66	3.15	0.18

Table 5.2-9

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. 0RB900

DATE 072381
RUN BY T.E. POLLAK

JITTER MODEL LSD900 PRCERR=5 ZG=.001
MSS FORCES MSS/RMS ALLOWABLES

COEFF MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
1 24	13.62	0.9676	1.75	0.33	0.58	1.16	0.36	0.37	6.57	0.51	1.11	3.80	0.26	0.71
1 25	13.62	0.9631	1.09	1.63	0.48	0.69	1.13	0.30	5.45	1.23	0.98	3.02	0.74	0.62
3 99	68.10	0.9613	0.37	0.37	0.49	0.19	0.19	0.24	2.60	6.17	0.38	1.25	4.23	0.18
4 126	95.34	0.9572	0.75	0.70	0.95	0.41	0.36	0.46	3.58	0.37	2.90	1.59	0.19	1.94

Table 5.2-10

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. 0RB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL L50900 PRERR=15 ZG=.01
MSS FORCES MSS/RMS ALLOWABLES

COEFF MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
3 105	68.10	0.8891	0.34	0.76	0.75	0.18	0.46	0.36	11.27	0.72	1.03	6.72	0.44	0.59
3 106	68.10	0.8845	0.26	0.31	0.53	0.18	0.16	0.28	3.56	0.30	0.34	1.63	0.15	0.16
3 108	68.10	0.8674	0.55	0.77	0.74	0.27	0.44	0.39	6.57	1.10	0.36	3.49	0.70	0.17
3 109	68.10	0.8507	0.32	0.18	0.44	0.18	0.10	0.23	3.49	0.74	0.29	1.60	0.26	0.15

Table 5.2-11

ORIGINAL PAGE 19
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

particular bandwidth. A detailed explanation of table format appears on Table 5.2-5. A derivation of the MSS experiment forcing function can be found in Reference 12. Considering the data presented, the impact of the predicted MSS response values can be reduced by an alteration of the allowable pixel error specification (see Table 5.2-4) from the current 0.30 values. Tables 5.2-12 and 5.2-13 present the only worst case single mode shift summaries which exist for TM peak allowables. These responses are representative of the order of magnitude of responses expected and confirmed in subsequent model configurations. Since these responses are within the capability of the ADS, future discussion of TM jitter magnitudes will be brief.

To consider the impact of single mode shifts, consider Figures 5.2-45a-b, 5.2-46a-b, and 5.2-47a-b. Depicted here are typical frequency response plots for a force/response at the MSS in the Theta X (θ_x) direction for three bandwidth conditions, 5%, 10%, and 15%. As can be seen, with increasing bandwidth (error) spreads an overlap condition (shaded area) develops, predominately at the higher harmonics due to the larger frequencies associated with the forcing harmonic. In evaluating placement of an offensive mode of the eigenvalue spectrum outside the respective harmonics, the overlap conditions and narrow corridors preclude effective movement. Reducing bandwidth spread compromises the structural unknowns associated with each spacecraft. Therefore, a statistical approach was implemented to ascertain the likelihood of any worst case occurrence. A discussion of the statistical approach method in jitter analysis follows.

RUN NO. 0RB900

DATE 072381
RUN BY T.E.POLLAK

JITTER MODEL LSD900 PRCERR=15 ZG=.001
TM FORCES TM/PEAK ALLOWABLES

COEFF	MODE	FCPS	RATIO	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
4	76	49 00	0.8952	5 63	5.74	1.72	3 99	3.97	1 14	1 50	2.96	0.72	0.80	1.78	0.40
4	81	49 00	0.8553	3 74	3 13	1.12	2.04	2 13	0.68	1 37	1.13	1.09	0.76	0.56	0.65

Table 5.2-12

ORIGINAL PAGE IS
OF POOR QUALITY

RUN NO. 088900

DATE 072381
RUN BY T.E. POLLAK


JITTER MODEL LSD900 PRCERR=15 ZG=.001
MSS FORCES TM/PEAK ALLOWABLES

COEFF MODE	FCPS	RAT10	P4TM	P5TM	P6TM	R4TM	R5TM	R6TM	P4MSS	P5MSS	P6MSS	R4MSS	R5MSS	R6MSS
2 48	40.86	1.1091	0.84	3.58	2.85	0.43	2.48	1.89	6.25	2.53	2.79	3.89	1.61	1.87
3 105	68.10	0.8891	1.25	6.62	4.13	0.62	4.59	2.72	94.55	5.71	7.92	65.54	3.90	5.38
3 107	68.10	0.8788	1.12	2.91	1.77	0.62	1.97	1.06	7.31	1.57	0.58	4.05	0.97	0.26
3 108	68.10	0.8674	3.15	6.05	4.75	2.04	4.19	3.15	46.86	10.75	1.26	31.85	7.43	0.70

Table 5.2-13

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY



5% BANDWIDTH

Figure 5.2-45a Typical Response Showing 5% Bandwidth for MSS

ORIGINAL PAGE IS
OF POOR QUALITY





Figure 5.2-45b




ORIGINAL PAGE IS
OF POOR QUALITY

10% Bandwidth


Figure 5.2-46a Typical Response Showing 10% Bandwidth for MSS

ORIGINAL PAGE IS
OF POOR QUALITY



10% BANDWIDTH

Figure 5.2-46b



15% Bandwidth

Figure 5.2-47a Typical Response Showing 15% Bandwidth for MSS

RESPONSE AT MSS THETA X




Figure 5.2-47b

A tabulation of LSD900 baseline jitter values (no mode shifts) is presented in Table 5.2-14 for $C/C_C = 0.001$ and in Table 5.2-15 for $C/C_C = 0.01$.

5.3 WORST CASE STATISTICAL ANALYSIS

Since a worst case analysis produces maximum jitter responses only when a modal frequency coincides exactly with a forcing harmonic frequency, a statistical analysis approach was developed to determine the probability of exceeding the MSS jitter budget. The analysis includes only those modes which both meet the $\pm 15\%$ bandwidth criteria and result in jitter RMS responses greater than the MSS allowables. From the selected set of worst cases, individual modes are shifted around each forcing frequency to obtain jitter responses and statistics in the θ_x , θ_y , θ_z directions at the MSS C.G.

Because an analytical model cannot be "tuned" to exactly match all measured test modes and frequencies, there is an uncertainty associated with the analytical predicted frequencies. Results from previous modal tests indicate that approximately 90% of the tuned model's modes were within 10% of the test frequencies. By assuming a Gaussian distribution for the predicted frequencies, this translates into predicting 98.6% of the modes to within 15% of the measured test frequencies, 90% of the modes to within 10% or 60% of the modes to within 5%. Figure 5.3-1 below shows the Gaussian probability density function for a single mode where 90% of the shaded area under the curve occurs between $.9 f_m$ and $1.1 f_m$ where f_m is a predicted frequency. Definitions for the mean & standard deviation are also shown.

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-14 LSD900 Baseline Jitter Predictions

Damping = 0.001

Forcing Location	Response Location	Jitter Values	
		Peak	RMS
TM θ_X	TM θ_X	1.3725	0.8445
	θ_Y	0.3404	0.2041
	θ_Z	0.2805	0.1453
	MSS θ_X	1.2063	0.7140
	θ_Y	0.6233	0.3585
	θ_Z	0.2691	0.1273
MSS θ_X	TM θ_X	0.3203	0.1854
	θ_Y	0.2033	0.1015
	θ_Z	0.4862	0.2389
	MSS θ_X	2.0945	1.1673
	θ_Y	0.3492	0.1818
	θ_Z	0.3228	0.1679

ORIGINAL PAGE IS
OF POOR QUALITY

Table 5.2-15 LSD900 Baseline Jitter Predictions

Damping = 0.01

Forcing Location	Response Location	Jitter Values	
		Peak	RMS
TM θ_X	TM θ_X	1.7215	0.9267
	θ_Y	0.3673	0.1638
	θ_Z	0.4895	0.2240
	MSS θ_X	1.2426	0.6459
	θ_Y	0.2682	0.1433
	θ_Z	0.3988	0.2144
MSS θ_X	TM θ_X	0.2636	0.1752
	θ_Y	0.1859	0.09626
	θ_Z	0.4465	0.2304
	MSS θ_X	2.3487	1.245
	θ_Y	0.1912	0.08936
	θ_Z	0.2711	0.1417

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-1

If the nominal orbital analysis (no shifted modes) results in no jitter responses greater than any of the allowable values, then for each selected worst case mode there can be found an upper (f_u), and lower (f_L) shifted frequency value which results in jitter equal to the allowables. As an example, let us assume that θ_{X0} is the maximum allowable RMS response for MSS response about the X-axis. When the modal frequency, f_M , shown in Figure 5.3-2 is shifted to the driving frequency, f_D , the response, θ_X , is much greater than θ_{X0} . When f_M is shifted to either the lower frequency, f_L , or the upper frequency, f_u , the response θ_X , exactly equals θ_{X0} . The probability that θ_X will be greater than θ_{X0} is given by the probability that f_M falls in the interval defined by f_L and f_u . This probability will be the shaded area under the normal density function shown in Figure 5.3-2.

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-2

Now, let A_i be the i th event that one mode when shifted in a specific harmonic results in jitter greater than θ_{XO} in the bandwidth defined by $f_L \leq f_M \leq f_u$. Defining $g_i(f)$ as the Gaussian probability density function for mode j as a function of frequency, the probability, $P[A_i]$, will be given by

$$P[A_i] = \int_{f_1}^{f_2} g_j(x) dx$$

Letting n_k equal the number of worst cases at the k th forcing harmonic frequency, the total number of A_i events, n , will be given by

$$n = \sum_k n_k$$

ORIGINAL PAGE 19
OF POOR QUALITY

for $k = 1$ to maximum number of forcing harmonics used in the analysis. Note that in the higher frequency ranges (above 50 Hz for TM), the $\pm 15\%$ modal frequency error causes modes to be shifted both to the lower and upper forcing frequencies for worst case analyses. If any single mode results in jitter values greater than the allowable in both harmonics, it is counted as two distinct events for the statistical analysis.

Defining the complement of $P[A_i]$ as

$$P[A_i]^C = 1 - P[A_i]$$

where $P[A_i]^C$ represents the probability that event A_i will not occur, the probability that none of the A_i 's will occur, $P[A]^C$, is given by the product of all the $P[A_i]^C$'s:

$$P[A]^C = \prod_i (P[A_i]^C)$$

The probability of at least one worst case occurring, $P[A]$, is given by the complement of $P[A]^C$:

$$P[A] = 1 - P[A]^C.$$

Using this statistical approach to describe jitter results provides additional insight for evaluating worst case responses. It allows us to assess jitter as a function of modal frequency and its relative location near a forcing harmonic. The closer a frequency is to a forcing harmonic, the more likely a worst case will occur. At the same time, the magnitude of the jitter response for a particular mode and the overlapping shifts at higher frequencies is accounted for.

ORIGINAL PAGE IS
OF POOR QUALITY

For this report, statistics were calculated using MSS allowables for jitter at the MSS due to both TM and MSS forces. Probabilities were calculated based on the MSS/RMS allowables for each axis of response (θ_x , θ_y , and θ_z). Initially the statistics were calculated using a value of $C/C_C = .001$. These results are shown in figures 5.3-3 to 5.3-8. In order to investigate the effects of damping, a final set of statistics was generated for $C/C_C = .01$ shown for MSS forcing in Figures 5.3-9 to 5.3-11. For $C/C_C = 0.01$ and TM forces, since no worst cases exist, no statistics are available.

Results show that jitter at the MSS due to TM forcing is highly unlikely to occur regardless of the damping values selected. Figure 5.3-6 shows the probability of exceeding the .3 pixel error in the θ_x direction due to TM forces to be .046. The probabilities for all other MSS responses due to TM are less than this value.

Results for jitter at the MSS due to MSS forcing show large changes in the probabilities when the jitter error is in the 1 to 4 arc-sec range. Figure 5.2-3 shows the probability of exceeding 1.5 arc-sec (.3 pixel error) in the θ_x direction is .34. If the allowable RMS jitter is raised to 3.14 arc-secs (.4 pixel error), the probability of exceeding this value is reduced to .093. A similar reduction is shown for the θ_y responses in Figure 5.3-4. A change from the .3 to .4 pixel allowables reduces the probability of exceedance from .094 to .027.

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-3

ORIGINAL PAGE 18
OF POOR QUALITY




Figure 5.3-4

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-5

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-6

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-7

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-8




Figure 5.3-9

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-10

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5.3-11

ORIGINAL PAGE IS
OF POOR QUALITY

A comparison of the MSS due to MSS statistics for 0.001 and 0.01 damping values shows little change in the 1 to 4 arc-second region for 0.40 pixel allowables. The higher damping values affect the statistics in the response regions above 10 arc-seconds. Results show that damping effects are most pronounced in determining MSS due to MSS statistics for the 0.30 pixel allowables.

6.0 REFERENCES

1. PIR U-1R4.-LS/D-921, "MSS/TM Orbital Jitter Analysis", T. E. Pollak/
E. J. Kuhar to J. Schumacher, 4/29/81.
2. Document No. 80SDS4227, "Landsat-D Deployed Solar Array Modal Test
Final Report", D. G. Breskman/P. T. Spykerman, June 1980.
3. PIR U-1R43-LS/D-1019, "Model Checkout Of "Latest" MMS Model",
C. Faust to J. Schumacher, 6/18/81.
4. Document No. 81SDS4217, "Landsat-D Deployed TDRSS Boom Modal Test
Final Report", R. T. Spykerman/T. E. Pollak, April, 1981.
5. PIR U-1R44-LS/D-870, "Boom Sensitivity Analysis", T. E. Pollak/
R. R. Kaufman to J. R. Schumacher, 10/7/80.
6. PIR U-1R43-LS/D-952, "Review of IM NASTRAN Model", C. Faust/H.
Vichnin to J. Schumacher, 12/8/80.
7. PIR U-1R43-LS/D-942, "Re-Calculation of Thematic Mapper Foot
Influence Coefficients", C. Faust to J. Schumacher, 11/12/80.
8. PIR U-1R43-LS/D-960, "Landsat-D Instrument Module Finite Element
Model", C. Faust to J. Schumacher, 1/22/81.
9. PIR U-1R43-LS/D-963; "Instrument Module Finite Element Model With
TRW Wideband Module Added", C. Faust to J. Schumacher, 1/27/81.
10. PIR U-1R43-LS/D-1018, "Landsat-D Instrument Module Finite Element
Model Update", M. Mangano to J. Schumacher, 6/16/81.
11. Document No. 81SDS4220, "Landsat-D Instrument Module Mini-Modal
Test Final Report", R. T. Spykerman/T. E. Pollak/D. G. Breskman,
May 1981.
12. Memo LS/D #572, "Experiment Forcing Function Preliminary Analysis",
J. M. Medaglia to T. Aepli, 11/16/79.